

1 LOCATION OF WATER WELL: County: Kingman		Fraction C 1/4 SE 1/4 NW 1/4	Section Number 17	Township Number T 30 S	Range Number R 10W E/W
Distance and direction from nearest town or city street address of well if located within city? 1 w of Nashville, Kansas					
2 WATER WELL OWNER: Erwin Hensiek RR#, St. Address, Box #: Nashville, Ks. City, State, ZIP Code: 67112		Hummon Corp. One Main Pl. Wichita, Ks. 67202		Hensiek No. 1 Board of Agriculture, Division of Water Resources Application Number: Unknown	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 135 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered: 165 ft. 2. 65 ft. 3. 7/25/84 ft. WELL'S STATIC WATER LEVEL: 65 ft. below land surface measured on mo/day/yr Pump test data: Well water was 60 gpm: Well water was 8 in. to 135 ft. and 8 in. to 135 ft. Est. Yield: 60 gpm: Well water was 8 in. to 135 ft. and 8 in. to 135 ft. Bore Hole Diameter: 8 in. to 135 ft. and 8 in. to 135 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter: 5 in. to 115 ft. Dia. 12 in. to 2.8 in. to Sch. 40 ft. Casing height above land surface: 12 in. weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40		CASING JOINTS: Glued X Clamped Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 115 ft. to 135 ft. From 115 ft. to 135 ft. From 115 ft. to 135 ft. From 115 ft. to 135 ft.		GRAVEL PACK INTERVALS: From 10 ft. to 135 ft. From 10 ft. to 135 ft. From 10 ft. to 135 ft. From 10 ft. to 135 ft.			
6 GROUT MATERIAL: <u>1 Neat cement</u> 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 <u>Oil well/Gas well</u> 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? South How many feet? 60			
FROM TO LITHOLOGIC LOG 0 70 Clay 70 135 Sand and Gravel		FROM TO LITHOLOGIC LOG			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/25/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 8/30/84 under the business name of Kellys Water Well Service by (signature) [Signature]		INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.			