WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1 1 1	County	Fraction		Section	number	Township number	Range number	
1. Location of well:	KINGMAN	SW 1/4 NE 1/4 SE	1/4	K	7	130 s	RIOW ED	
2. Distance and direction from nearest town or city: 15 1W 345 OF 3. Owner of well: CONE HEUMAN								
Street address of well location if in city: NASHVILLE, KS R.R. or street: City, state, zip code: NASHVILLE, KS								
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 32 in. Completion date		
N N						Well depth 100 ft. 11277		
NW NE WELL						Hollow rod Jetted Bored Reverse rotary		
X X						8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock		
						Lawn Oil field water Other		
¾						9. Casing: Material STL Height: Above or below Threaded Welded Surface 12 in.		
DRA INAGE						RMPIbs./ft.		
5. Type and color of material				From	То	Dia. Le in. to Le ft. dep Dia in. to ft. dep	th Wall Thickness: inches or	
3. Type and colds of material						10. Screen: Manufacturer's n	ame	
Soil, Sandy				0	2	Type Flor Plo Dia. 16" Slot/gauze Y8 Length 40' Set between 60 ft. and 160 ft.		
CLAY, TAN				2	11			
CLAY, TAN & SOME SAND				11	36	Gravel pack?	andft.	
				30	~0	11. Statie water level:	mo./day/yr.	
DOND, FINE TO COARSE GRAVEL				30	74	3.2 ft. below land sur		
CLY WHITE (THED)				79	87	12. Pumping level below land	I surfaces: ors. pumping 805 g.p.m.	
SWD FINETO COARE & MEDTO COARE GONEL				87	100	47 ft. after hrs. pumping 400 g.p.m. Estimated maximum yield g.p.m.		
CLY, TAN & SOME SAND				100	129	13. Water sample submitted:	mo./day/yr.	
SAND, FINE				129	130	Yes No 14. Well head completion:	Date	
Chy Tan	& WHITE (HA	PD)		130	137	Pitless adapter	12 Inches above grade	
Silvie Om				127	1/2	15. Well grouted? YSS With: Neat cementX	Bentonite Concrete	
State, Reb				(5)	145	Depth: From ft. to .		
						16. Nearest source of possible ft Direction		
						Well disinfected upon comple 17. Pump:	Not installed	
						Manufacturer's name E	www.	
						Model number	HP 60 Volts	
						Type: Submersible	X Turbine	
	7,70					Jet	Reciprocating	
(Use a second sheet if needed) 18. Elevation: 19. Remarks:						Centrifugal 20. Water well contractor's of	Other	
X10' CONCRETE SLAB					This well was drilled under m	y jurisdiction and this report		
18. Elevation: 19. Remarks: XIO CONCRETE SLAB Topography: AT SURFACE						is true to the best of my knowledge and belief. Couth June 325		
HIII Slope						Business name Address	Nor PRI License No.	
Upland Valley		•				Signed Authorized repr	resentative pate	
							TYVAK (