Shaufler (OWWO)	WATER WELL RECORD	Form WWC-5 KSA 82a	ı-1212 Plugo	ing Report
1 LOCATION OF WATER WELL:	Fraction SE	Section Number		Range Number
County: Kingman	C 1/4 SW 1/4 -	SE 1/4 23	T 30S S	R 10W E/W
Distance and direction from nearest town	or city street address of well if located	d within city?		
Distance and direction from nearest town or city street address of well if located within city?  WATER WELL OWNER: Oil Producers, Inc. of Kansas Contractor: D. R. Lauck Oil Company, Inc. RR#, St. Address, Box #: 1346 N. Woodlawn (P.O. Box 8647) Board of Agriculture, Division of Water Resources City, State, ZIP Code : Wichita, Kansas 67208 Application Number:  UCCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL. 100 ft. ELEVATION:  Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.  WELL'S STATIC WATER LEVEL35 ft. below land surface measured on mo/day/yr .6-12-77  Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. in. to .ft., and .in. to .ft.  WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
	2 Irrigation 4 Industrial  Was a chemical/bacteriological sample s			1 6
	nitted		ter Well Disinfected? Yes	
5 TYPE OF BLANK CASING USED:	5 Wrought iron		CASING JOINTS: Glue	
1 Steel 3 RMP (SR)	_	9 Other (specify below		ded
2 PVC 4 ABS	7 Fiberglass		Thre	paded
Blank casing diameter 5 ir	n. to ft., Dia	in. to	ft., Dia	in. to ft.
Casing height above land surface3.	' belowin., weight	<b>lbs</b> ./	ft. Wall thickness or gauge N	No
TYPE OF SCREEN OR PERFORATION		7 PVC	10 Asbestos-cem	· · · · · · · · · · · · · · · · · · ·
1 Steel 3 Stainless	steel 5 Fiberglass	8 RMP (SR)		)
2 Brass 4 Galvanized	d steel 6 Concrete tile	• •	12 None used (o	·
SCREEN OR PERFORATION OPENING	S ARE: 5 Gauze	ed wrapped	•	· · · · · · · · · · · · · · · · · · ·
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
	From ft. to			
GRAVEL PACK INTERVALS: From				
From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat ce				
Grout Intervals: From13ft. to3ft., Fromft. toft. to				
1 Septic tank 4 Lateral		11 Fuel	•	Dil well/Gas well
2 Sewer lines 5 Cess p	• •		•	
3 Watertight sewer lines 6 Seepag				Other (specify below)
Direction from well?  How many feet?				
FROM TO	LITHOLOGIC LOG	FROM TO	LITHOLOG	GIC LOG
100' 35' Sandy Grave	el 90 cu. ft.			GIC LOG
35' 13' Clay	30.47 cu. ft.			, ,
13' 3' Cement	2-1/3 sacks			ν
3' 0' Top Soil				
				<i>\</i> \
	S. S. Ling		Mark 1944 And Recorded	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was				
completed on (mo/day/year)8+1-84				
Water Well Contractor's License No				
under the business name of D. R. Lauck Oil Company, Inc. by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, undertine or patient answers. Send top				
three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section Topeka, IS 66620 Send one to WATER WELL OWNER and retain one for your records.				
7				
				Δ