

LOCATION OF WATER WELL:

Fraction

Section Number

Township Number

Range Number

County: Kingman $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$ 35T 30

S

R 10E W

Distance and direction from nearest town or city street address of well if located within city?

WATER WELL OWNER: Dale MorseRR#, St. Address, Box #: RT. 1, Box 60

Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Nashville, KS 67112

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 77 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr 7-24-92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 6 in. to 77 ft., and in. to ft.WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes ☒ No

TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded ☒Blank casing diameter 2 in. to 72 ft. Dia. in. to ft. Dia. in. to ft.Casing height above land surface: 24 in., weight Sched 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 72 ft. to 77 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 77 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 21.5 ft. From 21.5 ft. to 25 ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

NORTHHow many feet? 600+

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	Clay & Gravel			
10	15	Clay			
15	30	Clay with fine to Medium Sand			
30	40	Medium Sand			
40	60	Fine to Medium Sand			
60	70	Fine Sand			
70	76	Medium Sand			
76	77	Red Shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-24-92 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 334 This Water Well Record was completed on (mo/day/yr) 7-31-92under the business name of EWBANK INCby (signature) Dale Ewbank