


1 LOCATION OF WATER WELL: County: Barber Fraction: NW 1/4 SE 1/4 SE 1/4 Section Number: 20 Township Number: T 30 S Range Number: R 15 EW

Distance and direction from nearest town or city street address of well if located within city?
3 1/2 W 3 1/2 N Sun City

2 WATER WELL OWNER: Kansas Gas Supply Corp
 RR#, St. Address, Box #: Box 352 Pratt, Kans 67124 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Pratt, Kans 67124 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 69 ft. ELEVATION: 45 ft.

Depth(s) Groundwater Encountered: 1. 38 ft. 2. 25 ft. 3. 45 ft.

WELL'S STATIC WATER LEVEL: 3-11-82 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 15 gpm: Well water was 69 ft. after 9 hours pumping

Bore Hole Diameter: 9 in. to 69 ft., and 9 in. to 69 ft.

WELL WATER TO BE USED AS:
 1 Domestic 1 3 Feedlot 1 6 Oil field water supply 1 9 Dewatering 1
 2 Irrigation 1 4 Industrial 1 7 Lawn and garden only 1 10 Observation well 1

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 1 3 RMP (SR) 1 5 Wrought iron 1 8 Concrete tile 1 CASING JOINTS: Glued Clamped 1
 2 PVC 1 4 ABS 1 6 Asbestos-Cement 1 9 Other (specify below) 1 Welded 1
 Blank casing diameter: 5 in. to 1459 ft., Dia. 59 in. to 69 ft., Dia. 59 in. to 69 ft.

Casing height above land surface: 1459 in., weight 265 lbs./ft. Wall thickness or gauge No. 265

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 1 3 Stainless steel 1 5 Fiberglass 1 7 PVC 1 10 Asbestos-cement 1
 2 Brass 1 4 Galvanized steel 1 6 Concrete tile 1 8 RMP (SR) 1 11 Other (specify) 1
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 1 3 Mill slot 1 5 Gauzed wrapped 1 8 Saw cut 1 11 None (open hole) 1
 2 Louvered shutter 1 4 Key punched 1 6 Wire wrapped 1 9 Drilled holes 1
 SCREEN-PERFORATED INTERVALS: From 59 ft. to 69 ft., From 59 ft. to 69 ft., From 59 ft. to 69 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 69 ft., From 13 ft. to 69 ft., From 13 ft. to 69 ft.

6 GROUT MATERIAL: 1 Neat cement 1 2 Cement grout 1 3 Bentonite 1 4 Other 1

Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.

What is the nearest source of possible contamination:
 1 Septic tank 1 4 Lateral lines 1 7 Pit privy 1 10 Livestock pens 1 14 Abandoned water well 1
 2 Sewer lines 1 5 Cess pool 1 8 Sewage lagoon 1 11 Fuel storage 1 15 Oil well/Gas well 1
 3 Watertight sewer lines 1 6 Seepage pit 1 9 Feedyard 1 12 Fertilizer storage 1 16 Other (specify below) 1
 13 Insecticide storage 1

Direction from well? NW How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Soil			
4	20	Fine sand			
20	22	Clay			
22	39	Sand			
39	45	Clay			
45	60	medium to coarse sand			
60	69	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-11-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 3-27-82 under the business name of Lyman Bros by (signature) Richard Lyman

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 15 EWD SEC. 20 NW 1/4 SE 1/4 SE 1/4