USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number | Range number | |
|--|--------|--------------|-----|----------------|---|---|-----------------------|----------|
| 1. Location of well: | Kiowa | 1/4CSW 1/4S% | 1/4 | 3 | 0 | τ 30 s | R 17W E∧ | <i>,</i> |
| 2. Distance and direction from nearest town or city: 3. Owner of well: Abe: | | | | | rcrombie Drlg Co. | | | |
| Street address of well location if in city: | | | | street: | Rl | Great Bend, Ks. 67530 | | |
| Street address of well location if in city: Wilmore, Ks. City, state, | | | | | ne, rip code. | | | |
| 4. Locate with "X" in section below: N | | | | | 6. Bore hole dia. 8 in. Completion date Well depth 168 ft. 12-8-77 | | | |
| | | | | | | 7 Cable tool _XRotary Driven Dug | | |
| | | | | | | Hollow rod Jetted Bored Reverse rotary | | |
| | | | | | | 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock | | |
| | | | | | | | | |
| | | | | | | Lawn XOil field waterOther 9. Casing: Material Height: Above or 1605X | | |
| x | | | | | | Threaded Welded Surface 12 in . RMP PVC _X | | |
| s | | | | | | | | |
| ı ← 1 Mile → ı | | | | | | | | |
| 5. Type and color of material | | | | From | Та | 10. Screen: Manufacturer's name | | |
| Top Soil-Clay | | | | 0# | 60 | Jetstream Type | | |
| | | | | 1. | | | | |
| Sand | | | | 60 | 80 | | | |
| Sandy Clay | | | | 80 | 120 | | | |
| Sand | | | | 120 | 168 | 11. Static water level:ft. below land surf | ace Date 12-8-7 | 5. |
| | | | | | | 12. Pumping level below land | surfaces: | 1 |
| | | | | | | ft. after h | | |
| | | | | | | Estimated maximum yield | 50 g.p.n | |
| | | | | | | 13. Water sample submitted: | mo./day/y | r. |
| | | | | | | | Date | _ |
| | | | | | | 14. Well head completion: Pitless adapter | 12 Inches above grade | |
| | | | | | | 15. Well grouted? X | | |
| | | | | ļ | | With: Neat cement X Depth: From 0 ft. to | | |
| | | | | | | 16. Negrest source of possible ft. Direction S | contamination: ##0] | .] ' |
| | | | | | | Well disinfected upon comple | | 10 |
| | | | | | | 17. Pump: | Not installed | 77 |
| | | | | ļ | | Manufacturer's name Model number | HP Volts | - |
| | | | | | | | _ ft. capacityg.p.m | . Sm |
| | | | | | | Туре: | - 1. | |
| | | | | | Submersible Jet | Turbine Reciprocating | k | |
| (Use a second sheet if needed) | | | | | | Centrifugal | Other | 1 % C |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's c | | |
| | | | | | | This well was drilled under my is true to the best of my know | • | |
| Тородгарну: | | | | | Kellys Waterwell Ser 186 | | | |
| Hill Share | | | | | Business name License No. | | | |
| Slope | | | | | KILL D | Tee .8-21 | 7200 | |
| | | | | | | Signed Authorized repr | esentative | 15/E |