


LOCATION OF WATER WELL: County: Kiowa Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 5 Township Number: T 30 S Range Number: R 18 E

Distance and direction from nearest town or city street address of well if located within city?
115 2 W Greensburg Kans.

WATER WELL OWNER: Broce Construction
 #, St. Address, Box #: Dodge City Kans
 State, ZIP Code: Dodge City Kans Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL: 190 ft. ELEVATION: 190 ft.



Depth(s) Groundwater Encountered 1. 107 ft. 2. 107 ft. 3. 107 ft.
 WELL'S STATIC WATER LEVEL 107 ft. below land surface measured on mo/day/yr 3-7-85
 Pump test data: Well water was 107 ft. after 1 hours pumping 10 gpm
 Est. Yield 30 gpm. Well water was 107 ft. after 1 hours pumping 10 gpm
 Bore Hole Diameter: 8 3/4 in. to 190 ft., and 190 in. to 190 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Road Construction
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 107
 Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter 5 in. to 150 ft. Dia. 12 in. weight 12 lbs./ft. Wall thickness or gauge No. SDR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 30

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 150 ft. to 190 ft. From 140 ft. to 190 ft.
 GRAVEL PACK INTERVALS: From 140 ft. to 190 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 10 ft. to 20 ft. From 10 ft. to 20 ft.

What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) 18W

Direction from well? N E How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	105	tan clay			
105	141	Dirty Fine Sand			
141	169	Clay			
169	190	Gravel			

RECEIVED

JUL 09 1985

BUREAU OF OIL FIELD & ENVIRONMENTAL GEOLOGY

S
SW
SW
SW

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-7-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 7-6-85 under the business name of Carl Hayse Water Well Serv by (signature) Carl Hayse
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.