


1 LOCATION OF WATER WELL: County: Sioux Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 18 Township Number: T 30 S Range Number: R 18 SW

Distance and direction from nearest town or city street address of well if located within city?

1 W 115 GREENSBURG Kans.

2 WATER WELL OWNER: JIM GREENLEAF Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: GREENSBURG Kans Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 84 ft. 2. 84 ft. 3. 84 ft.  
 WELL'S STATIC WATER LEVEL: 84 ft. below land surface measured on mo/day/yr 3-2-83  
 Pump test data: Well water was 90 ft. after 1 hours pumping 5 gpm  
 Est. Yield 10 gpm; Well water was 90 ft. after 1 hours pumping 5 gpm  
 Bore Hole Diameter: 8 3/4 in. to 120 ft., and 120 in. to 120 ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    12 Other (Specify below)  
 2 Irrigation    4 Industrial    7 Lawn and garden only    10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel  3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
 7 Fiberglass Threaded X

Blank casing diameter: 5 in. to 90 ft., Dia. 90 in. to 90 ft., Dia. 90 in. to 90 ft.  
 Casing height above land surface: 12 in., weight 12 lbs./ft. Wall thickness or gauge No. SDR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass  8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) X  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped  8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) X

SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft., From 90 ft. to 110 ft., From 90 ft. to 110 ft.  
 GRAVEL PACK INTERVALS: From 75 ft. to 110 ft., From 75 ft. to 110 ft., From 75 ft. to 110 ft.

6 GROUT MATERIAL:  1 Neat cement  2 Cement grout 3 Bentonite 4 Other X  
 Grout Intervals: From 4 ft. to 15 ft., From 4 ft. to 15 ft., From 4 ft. to 15 ft., From 4 ft. to 15 ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well? 75 How many feet? NE

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	TOP			
2	15	Silt & Clay			
15	52	Tan Clay			
52	58	BROWN Clay			
58	77	Tan Clay			
77	89	Sand & Gravel			
89	102	Tan Clay			
102	109	Sand Gravel & White Clay			
109	120	Yellow Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-2-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 3-2-83 under the business name of Carl Kayse Water Well Serv by (signature) Carl Kayse

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 18 EW SEC. 18 SW 1/4 NE 1/4 NE 1/4