WATE	R WE	LL RECORD	Form W	WC-5	D	ivision of Wate	r Resources App. No	,.		
1 LOCATION OF WATER WELL:			Fraction						Range Number	
		manche	1/4 SW 1/4 SV					R 16	□E Z W	
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information: Latitude:				
	From Coldwater,10 Miles East, 1 mile South, 1/2 mile East, North					Longitude: (in decimal degrees)				
into.						Elevation:				
2 WATER WELL OWNER: Mule Creek Ranch (K. Leaper)						Datum: ☑ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:				
RR#, Street Address, Box #: 2852 HWY 160						GPS unit (Make/Model:)				
City, State, ZIP Code : Wilmore, KS 67155					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☑ 3-5 m, ☐ 5-15 m, ☐ >15 m					
3 LOCATE WELL										
WIT	HAN "Y	4 DEPTH OF	COMPLETED WEL							
WITH N 5 WIT								(3) tt.		
								ing	gpm	
יא	WNWNE EST. YIELD.5gpm. Well water was								gpm	
w									11	
	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well SW. SE. ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below									
\$\	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
BK !	Was a chemical/bacteriological sample submitted to Department? Yes No									
	S If yes, mo/day/yr sample was submitted									
water wen disinfected: W 165 100										
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other										
Casing diameter .5. in. to .58. ft., Diameter in. to .ft., Diameter in. to .ft.										
Casing height above land surface. 24 in., Weight SDR-17lbs./ft., Wall thickness or gauge No										
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes										
SCREEN-PERFORATED INTERVALS: From										
From										
GRAVEL PACK INTERVALS: From									ft.	
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other										
Grout Intervals: From .28 ft. to .0 ft., From ft. to ft. ft. o ft.										
What is the nearest source of possible contamination:										
H	Septic ta Sewer lin						Insecticide storage			
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Open Pasture										
Direction from well										
FROM 0	TO 5	LITHOLOG	IC LOG	FROM	TO	LITHO. LC	OG (cont.) or PLUC	GING I	NTERVALS	
5	17	Top Soil Sugar Sands	7.01.414	 						
17	23	GYP								
23	45	Sugar Sands								
45	78	Layered Shale								
				 						
			, PATIENT 8-1-4							
•						•				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, or plugged										
under my jurisdiction and was completed on (mo/day/year) 9/21/2011 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 665 This Water Well Record was completed on (mo/day/year) 11/21/2011										
under the business name of Pratt Well Service by (signature)										
INSTRUC	TIONS:	Use typewriter or ball point pen	. PLEASE PRESS FIRMLY	and PRINT cle	ariv. Plea	ase fill in blanks	and check the correct a	answers S	end three copies	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
http://www.kdheks.gov/waterwell/index.html.										