WATER WELL RECORD Form WWC-5 KSA 82a-1212

		KIOWA! SM					: Section N : 31						
		tion from nears	S		-		s of well if l						
	LL OWNER: Address,	ROY EV Box # :			265				iculture, D				
City, St	ate, ZIP (ode : BUCKL1	IN, KS	67	783 4-		Арр	lication	Number:		****		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:										2.	ft.	3	. 1
	; ; Wu	; ; ; NE					EL 61 ft. b : Well water					day/yr pumpin	
!	1	1 1	1 1	Estina	ated Yield	d g	om: Well water	was	ft. after		hours	pumpin	g ç
3		1 1	1 1						t., and	in.	to	ft.	
:	; ;	SE	; ; ; ;	WELL !	WATER TO E	BE USED AS	S: 01 DOMESTIC	;					
	5# !	1 1		Was a If yes	chemical/ s, mo/day/	/bacterio /yr sampl	logical sample e was submitte	submitte d	d to depart	ment? N Wate	o; rwel]	disin	fected? \
TYPE OF Blank ca Casing h	BLANK CAS sing diam neight abo SCREEN OR	ING USED: 02 PV(eter 5 ve land surface PERFORATION MAI	C in. to	o 102 in., : 07 P	CASI 2 ft., Di weig! VC	ING JOINT	 S: GLUED in. to f	t., Dia	in. t	 o			
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS sing diam neight abo SCREEN DR OR PERFORA	ING USED: 02 PV(eter 5 ve land surface	in. to 12 TERIAL RE:	o 102 in., : 07 Pt 08 St	CASI 2 ft., Di weig! VC AW CUT	ing JOINTS	S: GLUED in. to f lbs/ft. Wall ft., From	t., Dia thickness ft. to	in. t or gauge N	 o			
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS using diam neight abo SCREEN OR BR PERFORA PERFORATED	ING USED: 02 PV(eter 5 ve land surface PERFORATION MAT TION OPENINGS AF	C in. t 12 TERIAL RE:	o 102 in., : 07 Pt 08 St	CASI 2 ft., Di weig! VC AN CUT	ing JOINT: to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From	t., Dia thickness ft. to	in. t or gauge N	 o			
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN F GROUT MA Grout In What is	BLANK CAS using diam neight about SCREEN OR PERFORATED RAVEL PACK	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAI TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos	c in. to	o 10; in., : 07 P! 08 Si From From From	CASI 2 ft., Di weig! VC AN CUT 102 ft. t ft. t 25 ft. t	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From	t., Dia thickness ft. to ft. to ft. to	in. t or gauge N ft. ft. ft.	o 26	ft.	• many	
TYPE OF Blank ca Casing h TYPE OF SCREEN G SCREEN F GROUT MA Grout In	BLANK CAS sing diam peight above SCREEN OR OR PERFORATED PERFORATED RAVEL PACK ATERIAL ptervals: the neare on from we	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos 11? ALL	c in. t. 12 TERIAL RE:	o 10; in., : 07 P! 08 Si From From From	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.	• many NTERVAL	
TYPE OF Blank ca Casing h TYPE OF SCREEN G GREEN F GROUT MA GROUT In What is Directic	BLANK CAS using diam neight abou SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neare on from we TO 14	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAI TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos 11? ALL ; SILT & SAND ;	c in. t. 12 TERIAL RE:	o 102 in., : 07 Pl 08 Si From From From From Contain	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN G SCREEN F GROUT MA GROUT MA GROUT In What is Directic	BLANK CAS using diam neight abou SCREEN OR OR PERFORATED RAVEL PACK ATERIAL ntervals: the neare on from we 14	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos 11? ALL ; SILT & SAND ; TAN CLAY	c in. to to to LIT	o 10; in., : 07 Pt 08 Si From From From From Contain	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN GOT MAGE OF GROUT MAGE OF THE CASE OF	BLANK CAS using diam usight about SCREEN OR OR PERFORATED RAVEL PACK ATERIAL utervals: the neare on from we TO 14	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos 11? ALL SILT & SAND TAN CLAY O5 SAND AND	c in. to to to LIT	o 10; in., : 07 Pt 08 Si From From From From Contain	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN G SCREEN F GROUT MA Grout Ir What is Directic FROM 1	BLANK CAS sing diam neight abo SCREEN OR OR PERFORATED RAVEL PACK STERIAL netervals: the neare on from we 14 28 55 74	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: O3 BENTONITE From ft. st source of pos 11? ALL : SILT & SAND : TAN CLAY : O5 SAND AND : TAN CLAY	c in. t. 12 TERIAL RE: to ssible LIT	o 10; in., : 07 Pt 08 Si From From From From Contain	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN G SCREEN F GROUT MA Grout Ir What is Directic	BLANK CAS sing diam neight abo SCREEN OR OR PERFORATED RAVEL PACK STERIAL otervals: the neare on from we 14 28 55 74 81	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: 03 BENTONITE From ft. st source of pos 11? ALL SILT & SAND TAN CLAY O5 SAND AND	to ssible	o 10; in., : 07 Pt 08 Si From From From From Contain	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN FOR	BLANK CAS using diam usight about SCREEN OR OR PERFORATED RAVEL PACK ATERIAL utervals: the neare on from we 14 28 55 74 81 100 110	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAI TION OPENINGS AF INTERVALS: INTERVALS: O3 BENTONITE From ft. st source of pos 11? ALL SILT & SAND TAN CLAY O5 SAND AND TAN CLAY HITE CLAY SI WHITE CLAY SI WHITE CLAY SI	to ssible LIT	o 102 in., : 07 Pl 08 S/ From From From From Contain HOLOGI	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN OF SCREEN F GROUT MA GROUT IN What is Directic FROM : 1 14 28 55 74 81	BLANK CAS sing diam neight abo SCREEN OR OR PERFORATED RAVEL PACK ATERIAL ntervals: the neare on from we 14 28 55 74 81 100	ING USED: 02 PVC eter 5 ve land surface PERFORATION MAT TION OPENINGS AF INTERVALS: INTERVALS: O3 BENTONITE From ft. st source of pos 11? ALL TAN CLAY O5 SAND AND TAN CLAY GREY CLAY CLE UNITE CLAY SE	to ssible LIT	o 102 in., : 07 Pl 08 S/ From From From From Contain HOLOGI	CASI 2 ft., Di weig! VC AN CUT 102 ft. f ft. f 25 ft. f	ing JOINTS ia ht to 112 to 112 to 112	S: 6LUED in. to f lbs/ft. Wall ft., From ft., From ft., From ft., From to ft.	ft. to ft. to ft. to ft. to	in. to or gauge N ft. ft. ft. ft. ft.	o o . 26	ft.		

Water Well Contractor's License No. 224 This Water Well Record was completed on impo/day/yr) 05/10/94

under the business name of CARL HAYSE WATER WELL SVC