

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

|  |                                  |                      |                           |                        |
|--|----------------------------------|----------------------|---------------------------|------------------------|
| 1 LOCATION OF WATER WELL:<br>COUNTY: CLARK | Fraction<br>SE 1/4 SW 1/4 NW 1/4 | Section Number<br>11 | Township Number<br>T 30 S | Range Number<br>R 22 W |
|--|----------------------------------|----------------------|---------------------------|------------------------|

Distance and direction from nearest town or city street address of well if located within city?  
4 MILES WEST, 6 MILES SOUTH OF BUCKLIN

2 WATER WELL OWNER: THOROUGHbred & ASSOC  
RR#, St. Address, Box # : 8100 E. 22ND ST. W.  
City, State, ZIP code : WICHITA, KS 67226-  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH  
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 185 ELEVATION: 0  
Depth(s) Groundwater Encountered 1. 130 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr 01/28/08  
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 8.75 in. to 185 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: OIL FIELD

Was a chemical/bacteriological sample submitted to department? No ;  
If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED  
Blank casing diameter 5 in. to 135 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
Casing height above land surface 24 in., weight 0 lbs/ft. Wall thickness or gauge No. 26  
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

|                              |                          |                     |
|------------------------------|--------------------------|---------------------|
| SCREEN PERFORATED INTERVALS: | From 135 ft. to 175 ft., | From 0 ft. to 0 ft. |
|                              | From 0 ft. to 0 ft.,     | From 0 ft. to 0 ft. |
| GRAVEL PACK INTERVALS:       | From 25 ft. to 185 ft.,  | From 0 ft. to 0 ft. |
|                              | From 0 ft. to 0 ft.,     | From 0 ft. to 0 ft. |

6 GROUT MATERIAL BENTONITE  
Grout Intervals: From 1 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
What is the nearest source of possible contamination: SEPTIC TANK  
Direction from well? NORTHEAST How many feet? 2000

| FROM | TO  | LITHOLOGIC LOG  | FROM | TO | PLUGGING INTERVALS |
|------|-----|-----------------|------|----|--------------------|
| 0    | 86  | TAN CLAY        |      |    |                    |
| 86   | 152 | SAND AND GRAVEL |      |    |                    |
| 152  | 158 | TAN CLAY        |      |    |                    |
| 158  | 165 | SAND AND GRAVEL |      |    |                    |
| 165  | 184 | TAN SANDY CLAY  |      |    |                    |
| 184  | 185 | GRAY SHALE      |      |    |                    |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 01/28/08 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 653 This Water Well Record was completed on (mo/day/yr) 01/14/08  
under the business name of DAN HAYSE WATER WELL SERV by (signature) *Dan Hayse*