COUNTY:		ELLI : ;	SE	1/4 NE	E 1/4	4 NW	1/4	: Sect:	ion Numb	er 	Township				
B S. 3 E	. OF KINGS	ion from ne OOWN, KS													
WATER WE	LL OWNER:	CAF Box # : R.I	RL SCOT								culture.				
City, St	ate, ZIP c	ode : KII	46SDOWN	i, KS	6785	8-			Applic	ation N	umber:				
LOCATE N	VELL'S LOCA	TION WITH BOX:		; 4 D	EPTH OF	COMPLET	TED WEL	L 115	ELE	VATION:		2.	ft.	3	
\ ! !		: -: NE -													
1 1	# 1	1	3	! Est	imated	Yield	āb	on: Well	water wa	35	ft. afte	r	hours	pumpin	ıg
		-	E	: Bor	e Hole	Diameter	r	8.75	in. to	115 ft	, and	in.	to	ft.	•
1	6.7 ;	-; SE -	1 1	; WEL	L WATER	TO BE I	USED AS	3: 01 DOM	1ESTIC						
						vical/ha	ctorio!	Innical a	randia ci	uhmitta	to denar	tment?	No :		
/ !	BLANK CASI	NG USED: 02	PVC in	; If to	yes, mo	cay/yr Casing ., Dia	JOINTS	e was sul S: GLUED in. to	bmitted ft.	, Dia	in.	Wate to	er wel	l disir	nfected?
/ ; - ;- TYPE OF Blank c Casing TYPE OF	BLANK CASI asing diame height abov SCREEN OR	 - NG USED: 02	PVC in face	. to 18 in.	95 ft.	CASING , Dia weight	JOINTS	e was sul S: GLUED in. to	bmitted ft.	, Dia	in.	Wate to	er wel	l disin	nfected?
TYPE OF Blank c Casing TYPE OF SCREEN	BLANK CASI asing diame height abov SCREEN OR OR PERFORA	NG USED: 02 eter 5 re land surf	PVC in ace MATER	. to 18 in. IAL: 0	95 ft. ,, 7 PVC B SAN CO	CASING ., Dia weight UT ft. to	JOINTS	S: GLUED in. to lbs/ft.	bmitted ft. Wall th	. Dia ickness	in. or gauge ft.	to No. 26	er wel	l disin	nfected?
TYPE OF Blank c Casing TYPE OF SCREEN	BLANK CASI asing diame height abov SCREEN OR OR PERFORA	NG USED: 02 PERFORATION	PVC in face MATER	; If ; . to 18 in. IAL: 0: From	95 ft. ,, 7 PVC B SAW CI	CASING ., Dia weight UT ft. to ft. to	JOINTS	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro	bmitted ft. Wall th	, Dia ickness ft. to ft. to ft. to	in. or gauge ft. ft. ft.	to No. 26	er wel	l disin	nfected?
TYPE OF Blank c Casing TYPE OF SCREEN SCREEN GROUT M Grout I	BLANK CASI asing diame height abov SCREEN OR OR PERFORA PERFORATED SRAVEL PACK	NG USED: 02 PERFORATION TON OPENING INTERVALS: INTERVALS: 03 BENTONI From 1	PVC in face MATER SS ARE:	; If ; . to . 18 in. IAL: 0; . Of Froi Froi Froi	95 ft	CASING ., Dia weight UT ft. to ft. to ft. to ft. to	JOINTS 115 115	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro	ft. Wall th	, Dia ickness ft. to ft. to ft. to ft. to	in. or gauge ft. ft. ft.	to No. 26	er wel	l disir	nfected?
TYPE OF Blank c Casing TYPE OF SCREEN SCREEN GROUT M Grout I What is	BLANK CASI asing diame height abov SCREEN OR OR PERFORA PERFORATED SRAVEL PACK	NG USED: 02 eter 5 re land surf PERFORATION ION OPENING INTERVALS: INTERVALS: 03 BENTONI From 1 st source of	PVC in face MATER SS ARE:	; If ; . to . 18 in. IAL: 0; . Of Froi Froi Froi	95 ft	CASING ., Dia weight UT ft. to ft. to ft. to ft. to ft. to	JOINTS 115 115 ft.	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro ft., Fro	ft.	, Dia ickness ft. to ft. to ft. to	in. or gauge ft. ft. ft. ft.	to No. 26	ft.		fected?
/ : TYPE OF Blank c Casing TYPE OF SCREEN SCREEN GROUT M Grout I What is Directi FROM 38	BLANK CASI asing diame height abov SCREEN OR OR PERFORATED FRAVEL PACK MATERIAL Intervals: the neare ion from we TO 38 ; 115	NG USED: 02 ter 5 re land surf PERFORATION ION OPENING INTERVALS: INTERVALS: O3 BENTONI From 1 st source of 11? ALLL TAN CLAY O5 SAND	PVC in face MATER SS ARE:	. to 18 in. IAL: 0: From From From From From LITHOL	95 ft. 7 PVC 8 SAW CI m 95 m 25 m	CASING ., Dia weight UT ft. to ft. to ft. to ft. to ft. to	JOINTS 115 115 ft.	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro	ft.	, Dia ickness ft. to ft. to ft. to ft. to	in. or gauge ft. ft. ft. ft.	to No. 26	ft.		feet?
/ : TYPE OF Blank c Casing TYPE OF SCREEN SCREEN GROUT M Grout I What is Directi FROM 38	BLANK CASI asing diame height abov SCREEN OR OR PERFORATED FRAVEL PACK MATERIAL Intervals: the neare ion from we TO 38 ; 115	NG USED: 02 ter 5 re land surt PERFORATION TON OPENING INTERVALS: INTERVALS: O3 BENTONIT From 1 st source of	PVC in face MATER SS ARE:	. to 18 in. IAL: 0: From From From From From LITHOL	95 ft. 7 PVC 8 SAW CI m 95 m 25 m	CASING ., Dia weight UT ft. to ft. to ft. to ft. to ft. to	JOINTS 115 115 ft.	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro ft., Fro	ft.	, Dia ickness ft. to ft. to ft. to ft. to	in. or gauge ft. ft. ft. ft.	to No. 26	ft.	ew many	feet?
TYPE OF Blank c Casing TYPE OF SCREEN SCREEN GROUT M Grout I What is Directi	BLANK CASI asing diame height abov SCREEN OR OR PERFORATED FRAVEL PACK MATERIAL Intervals: the neare ion from we TO 38 ; 115	NG USED: 02 ter 5 re land surf PERFORATION ION OPENING INTERVALS: INTERVALS: O3 BENTONI From 1 st source of 11? ALLL TAN CLAY O5 SAND	PVC in face MATER SS ARE:	. to 18 in. IAL: 0: From From From From From LITHOL	95 ft. 7 PVC 8 SAW CI m 95 m 25 m	CASING ., Dia weight UT ft. to ft. to ft. to ft. to ft. to	JOINTS 115 115 ft.	S: GLUED in. to lbs/ft. ft., Fro ft., Fro ft., Fro ft., Fro	ft.	, Dia ickness ft. to ft. to ft. to ft. to	in. or gauge ft. ft. ft. ft.	to No. 26	ft.	ew many	feet?

Water Well Contractor's License No. 224

This Water Well Record was completed on (mo/day/yr) 08/29/93

by (signature)

completed on (mo/day/year) 8-/23/93 and this record is true to the best of my knowledge and belief. Kansas

under the business name of CARL HAYSE WATER WELL SVC