

1 LOCATION OF WATER WELL: County: CLARK		Fraction SE 1/4 SE 1/4 SE 1/4		Section Number 19		Township Number T 30 S		Range Number R 23 E/W	
Distance and direction from nearest town or city street address of well if located within city? 5 South and 2 East of Bloom, Kansas									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Mr. Gary Esplund Minneola, Kansas 67865							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Slope Depth(s) Groundwater Encountered 1. Not available ft. 2. Not available ft. 3. Not available ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr Dec. 12, 1985 Pump test data: Well water was Not available ft. after Not available hours pumping Not available gpm Est. Yield 30 gpm: Well water was Not available ft. after Not available hours pumping Not available gpm Bore Hole Diameter 9 7/8 in. to 40 ft. and Not available in. to Not available ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) XX PVC 4 ABS Blank casing diameter 5 in. to 20 ft., Dia. Not available in. to Not available ft., Dia. Not available in. to Not available ft. Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: XX PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped XX Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From Not available ft. to Not available ft. GRAVEL PACK INTERVALS: From 14 ft. to 40 ft., From Not available ft. to Not available ft.							
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 14 ft., From Not available ft. to Not available ft., From Not available ft. to Not available ft. What is the nearest source of possible contamination: XX Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? South How many feet? 100									
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG							
0 4 Topsoil									
4 10 Fine Sand									
10 31 Med. to Lar. Sand & Gravel									
31 40 Clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) December 12, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) December 13, 1985 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									

800000000000-50