COUNTY:	013 CLAR	 K METT:	; SE	1/4 NW	1/4 SW	1/4	; Section ; <b>24</b>		: Township	Number 5	1	Range i	Numper ₩ 
Distance	and dire		nearest		city street								
	LL OWNER: Address,	Box # :			070				iculture, Di				
·		code : B	UCKLIN,	KS	-		Ар	plication	Number:				
					PTH OF COMPL pth(s) Groun					2.	ft.	3.	- <b></b>
\	; ; ; ;	NE	1	9 1	'S STATIC WA Pump t				surface mea			day/yr pumping	
!	: : (4M	; NE	-		mated Yield	gpm	ı: Well wate	r was	ft. after	ħ	nours	pumping	g
				E ! Bore	Hole Diamet	er	8.75 in.	to 40 f	t., and	in. t	te	ft.	
	_ <b>%</b>	; ; ;	, ,	; WELL	WATER TO BE	USED AS:	01 DOMESTI	С					
1	1	!!!	1	; Was	a chemical/b	acteriolo	gical sampl	e submitte	d to depart	ment? No	;	dinin <b>i</b>	artad? W
TYPE OF	\ BLANK CAS	- ING USED: 0	)2 PVC	!	es, mo/day/yCASIN 30 ft., Dia weight	r sample  6 JOINTS:	GLUED						
TYPE OF Blank ca Casing h	BLANK CAS sing diam eight abo SCREEN OR	- ING USED: 0	)2 PVC i in face	. to 12 in., IAL: 07	CASIN 30 ft., Dia weight PVC	r sample  6 JOINTS:	GLUED						
TYPE OF STANK CASING HISTORY OF SCREEN OF	BLANK CAS sing diam eight abo SCREEN OR R PERFORA	ING USED: 0 eter 5 ve land sur	)2 PVC ) in face )N MATER	. to 12 in., IAL: 07 i	CASIN 30 ft., Dia weight PVC SAN CUT	r sample	GLUED to ss/ft. Wall	ft., Dia thickness	in. to				
TYPE OF I Blank ca Casing h TYPE OF I SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORA	ING USED: 0 eter 5 ve land sur PERFORATIO	O2 PVC inface ON MATER	. to 12 in., IAL: 07 i	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to	r sample	GLUED  i. to ss/ft. Wall , From, From, From	ft., Dia thickness	in. to				
TYPE OF DESCREEN OF SCREEN	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals:	ING USED: O eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTONI	PVC in face ON MATER IGS ARE:	. to 12 in., IAL: 07 08 From From From From 20 f	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  to s/ft. Wall  , From , From , From	ft., Dia thickness ft. to ft. to ft. to	in. to or gauge No ft. ft. ft.		ft.		
TYPE OF Dank care Casing he Type OF SCREEN OF SCREEN PER GROUT MAGROUT IN What is	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals:	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTONI From st source of	PVC in face ON MATER IGS ARE:	. to 12 in., IAL: 07 08 From From From From 20 f	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  to s/ft. Wall  , From , From , From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft.	o o o o o o o o o o o o o o o o o o o	ft.	many f	
TYPE OF DESCREEN OF SCREEN PORT MAGENT MAGEN TO SCREEN PORT MAGEN TO SCREEN PORT MAGENTAL TO SCREEN PORT MAGENT MA	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTONI From st source of	22 PVC i in face ON MATER IGS ARE:	. to 12 in., IAL: 07 08 From From From From 20 f	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  to s/ft. Wall  , From , From , From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.		
TYPE OF Blank cal Casing h TYPE OF SCREEN OF SCREEN P  GROUT MA GROUT MA Grout In What is Directio	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare n from we	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTONI From st source of	22 PVC i in face ON MATER IGS ARE:  ITE ft. to of possi	. to 12 in., IAL: 07 08 From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	
TYPE OF SPRING OF SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we 2 15 17	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS:  03 BENTONI From st source of 11? ALL  I SILT & S I TAN CLAY O5 SAND	22 PVC inface N MATER IGS ARE:  ITE ft. to of possi	. to 12 in., IAL: 07 08 From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	
TYPE OF Blank cal Casing h TYPE OF SCREEN OF SCREEN P  GROUT MA GROUT MA Grout In What is Direction  FROM :  2 : 15 : 17 :	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we TO 2 15 17 23	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS:  O3 BENTONI From st source 0 11? ALL  SILT & S TAN CLAY O5 SAND TAN CLAY	PVC in face ON MATER IGS ARE:	From From From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	
TYPE OF SPRING OF SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we 2 15 17	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS:  03 BENTONI From st source of 11? ALL  I SILT & S I TAN CLAY O5 SAND	PVC in face ON MATER HIS ARE:	From From From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	
TYPE OF Blank cal Casing hory FROM GROUT MA Grout In What is Direction FROM 15 17 123 1	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS:  O3 BENTONI From st source of 11? ALL  SILT & S TAN CLAY O5 SAND TAN CLAY O5 SAND	PVC in face ON MATER HIS ARE:	From From From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	
TYPE OF Blank cal Casing h TYPE OF SCREEN OF SCREEN P  GROUT MA GROUT MA Grout In What is Direction  FROM :  15 : 17 : 23 :	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK TERIAL tervals: the neare n from we	ING USED: 0 eter 5 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS:  O3 BENTONI From st source of 11? ALL  SILT & S TAN CLAY O5 SAND TAN CLAY O5 SAND	PVC in face ON MATER HIS ARE:	From From From From From From From From	CASIN 30 ft., Dia weight PVC SAN CUT  30 ft. to ft. to 20 ft. to ft. to	r sample G JOINTS: in lb 40 ft ft ft. t	GLUED  i. to ps/ft. Wall  i., From i., From i., From i., From i., From i., From	ft., Dia thickness ft. to ft. to ft. to ft. to	in. to or gauge No ft. ft. ft. ft. ft.	o 26	ft.	many f	

77 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well must be completed on (mo/day/year) 6 /3 /91 and this record is true to the best of my knowledge and beliet. Names water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 06/10/91 by (signature) by (signature)