WATER WELL REC	CORD Form WWC-5 Correction Change in Well Use		ision of Water urces App. No.		Well ID #7	
	ATER WELL: Fraction		ion Number	Township Number	er Range Number	
County: Clark	SW 1/4 SW 1/4		24	T 30 S	R 25 □ E ⋈ W	
2 WELL OWNER: Last Name:       First:       Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection):       If at owner's address, check here:       □         Business:       City of Minneola       4 direction from nearest town or intersection):       If at owner's address, check here:       □         Address:       PO Box 156       Approximately 1 mile south of Minneola.         City:       Minneola       State: KS       ZIP: 67865						
3 LOCATE WELL	4 DEPTH OF COMPLETED WE	L.L. 150 ft	5 Latitude	. 37 42246	(desimal desures)	
WITH "X" IN SECTION BOX:  N NWNE  E SWSE	Depth(s) Groundwater Encountered: 1)  2)  ft. 3)  WELL'S STATIC WATER LEVEL:  below land surface, measured on (mo-day-yr)  above land surface, measured on (mo-day-yr)  Pump test data: Well water was  after hours pumping gpm  Well water was  ft.  after hours pumping gpm		S Latitude: 37.42246 (decimal degrees)   Longitude: -100.014874 (decimal degrees)   Horizontal Datum.			
S	Estimated Yield: gpm Bore Hole Diameter: in. to		6 Elevation	n: Unknown ft.  Land Survey	GPS Topographic Map	
1 mile	in. to					
7 WELL WATER TO BE U  1. Domestic:  Household  Lawn & Garden  Livestock  Irrigation  Feedlot	5. Public Water Supply: well 6. Dewatering: how many we 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: Air Sparge	ID #7 ills? well ID /apor Extraction	10. Oil F 11. Test Hol Casec 12. Geother a) Close b) Open	ield Water Supply: le: le: well ID l	ase Geotechnical	
Was a chemical/bacteriological sample submitted to KDHE?						
8 TYPE OF CASING USED: Steel PVC CASING JOINTS: Glued Clamped Welded Threaded Other Flush Joint Casing diameter 14 in. to 106.90 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in. Weight 12.53 lbs./ft. Wall thickness or gauge No. 437  TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:  Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)  Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)  SCREEN-PERFORATED INTERVALS: From 108.40 ft. to 150 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 10 ft. to 150 ft., From ft. to ft.						
9 GROUT MATERIAL: Neat cement Cement Grout Bentonite Other						
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 10 ft., From ft. to ft.  Nearest source of possible contamination:  Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage  Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well  Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well  Other (Specify) None Known						
Direction from well?  10 FROM TO	Distance fro	om well?	TO LI	THO LOG (cont.) on	PLUGGING INTERVALS	
In	stalled 14" PVC Liner with Stainless Steel Scre 16" Steel Casing		TO LI	THO. LOG (cont.) or	PLOGUING INTERVALS	
To	op of casing set flush with existing well block					
		NY ,				
Notes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo-day-year) 11-1-2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo-day-year) 11-8-2021 under the business name of Clarke Well & Equipment, Inc.  Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,						
1000 SW Jackson St.	1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.					
visit us at http://www.kdneks.	.izov/waterweii/index.ntmi	KSA 82a-1212			Revised 7/10/2015	