


1 LOCATION OF WATER WELL: County: CLARK Fraction: SE 1/4 SE 1/4 NW 1/4 Section Number: 3 Township Number: T 30 S Range Number: R 25 EW

Distance and direction from nearest town or city street address of well if located within city?
2 W milled 1 1/2 W 1/4 S

2 WATER WELL OWNER: Murfin Drilling Co Boucher
 RR#, St. Address, Box #: Bq 183
 City, State, ZIP Code: PAATH, Ks. 67124
 Board of Agriculture, Division of Water Resources
 Application Number: 783-176

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 160' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 75' ft. 2. 75' ft. 3. 75' ft.
 WELL'S STATIC WATER LEVEL: 75' ft. below land surface measured on mo/day/yr 5/10/83
 Pump test data: Well water was 150 ft. after 2 hours pumping 30 gpm
 Est. Yield: 30 gpm. Well water was 150 ft. after 2 hours pumping 30 gpm
 Bore Hole Diameter: 9 in. to 160 ft., and 160 in. to 160 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes 8 No 8; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes 8 No 8

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) 10 Asbestos-cement 11 Injection well 12 Other (Specify below)
 Blank casing diameter: 3 in. to 8-75 ft., Dia. 14 in. to 200 lbs./ft. Wall thickness or gauge No. 0.265
 Casing height above land surface: 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 RMP (SR) 8 PVC 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 75 ft. to 160 ft., From 75 ft. to 160 ft., From 75 ft. to 160 ft., From 75 ft. to 160 ft.
 GRAVEL PACK INTERVALS: From 70 ft. to 160 ft., From 70 ft. to 160 ft., From 70 ft. to 160 ft., From 70 ft. to 160 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? EAST How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	75	overburden			
75	80	01 clay			
80	100	01 med. sand + clay			
100	140	01 fine sand + clay			
140	160	01 Blue Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 5/10/83 under the business name of TSW Water Well Service by (signature) C. D. Wagonseller/AW
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
 T 30
 R 25
 SEC. 3
 SE 1/4
 SE 1/4
 NW 1/4