


1 LOCATION OF WATER WELL: County: Clark Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 3 Township Number: T 30 S Range Number: R 25 E/W

Distance and direction from nearest town or city street address of well if located within city?
2N 1 1/2 W 3/4 NE Minneola, KS

2 WATER WELL OWNER: Mildred Fager Ladd Pet.
 RR#, St. Address, Box # :
 City, State, ZIP Code : Wichita KS 67202 Board of Agriculture, Division of Water Resources
 Application Number: 82-575

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 165 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 75 ft. 2. 75 ft. 3. 75 ft.
 WELL'S STATIC WATER LEVEL: 75 ft. below land surface measured on 11/20/82
 Pump test data: Well water was 84 ft. after 2 hours pumping 60 gpm
 Est. Yield: 80 gpm Well water was 84 ft. after 2 hours pumping 60 gpm
 Bore Hole Diameter: 9 in. to 165 ft., and 9 in. to 165 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 65 ft., Dia. 5 in. to 65 ft., Dia. 5 in. to 65 ft.
 Casing height above land surface: 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0-265
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 65 ft. to 165 ft., From 65 ft. to 165 ft., From 65 ft. to 165 ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 165 ft., From 30 ft. to 165 ft., From 30 ft. to 165 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 220

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	75	Overburden			
75	100	Fine Sand + clay			
100	120	Fine Sand + clay			
120	155	Fine Sand + clay			
155	165	Blue clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/20/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 11/20/82 under the business name of T & W Water Well Service by (signature) C. W. Wageman

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 25 EW 3 SEC. 3 1/4 1/4