WATER WELL RECORD	Form WWC-5		Resources App. No		
1 LOCATION OF WATER WELL: County:	Fraction 1/4 NE1/4 NE1/4 NW/4	Section Number	Township No. T 30 S		
Street/Rural Address of Well Location; if unknown, distance & direction		Global Positioning			
from nearest town or intersection: If at				(in decimal degrees)	
			Longitude: (in decimal degrees)		
1 Mile North of Forder		Elevation:			
111/10/10/17/1 6/	100984	— <u>Datum</u> : ☐ WGS 84	, 🔲 NAD 83, 🔲	NAD 27	
2 WATER WELL OWNER: Kei	n whitney	Collection Method:			
RR#, Street Address, Box #: 100 E 10 th Ave		☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code :	lev, 14 67844				
St. Accuracy:					
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	66 ft.			
SECTION BOX: Depth(s) Groun	Depth(s) Groundwater Encountered (1)				
N WELL'S STAT	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr				
Pum	Pump test data: Well water wasft. after hours pumping gpm				
EST. YIELD	EST. YIELD. 5. O. gpm. Well water was				
W Bore Hole Diameter 9.14. in. to					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
s If yes, mo/day/yr sample was submitted					
mile Water well disinfected? Yes \[\subseteq \ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Solution Clamped Welded Threaded Casing diameter In. to I					
Casing trianteter					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel YVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.					
SCREEN-PERFORATED INTERVALS:	From	ft., From	ft. to	o ft.	
GRAVEL PACK INTERVALS.	From 20 ft to 20	76 It., From	It. to	o ft.	
GRAVEL PACK INTERVALS: From. ft. to ft. from.					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral li	nes Pit privy Livestock	ens Insecticide s	storage	er (specify below)	
Sewer lines Cesspool	Sewage lagoon Fuel storag	e Abandoned	water well	(1)	
Watertight sewer lines Seepage			well ,		
FROM TO LITHOLOG		from well			
	GIC LOG FROM	TO LITHO. LO	G (cont.) or PLUC	GGING INTERVALS	
7 30 R					
20 67 Gray Clas					
17 70 6 //					
75 84 Gray Clay					
84 107 Blue clay					
107 190 Clay w/ Fine	to Med Sand Laypus				
84 107 Blue Clay 107 190 Clay of Fine 190 220 Gray & Yellow	(2 m				
170 0749 (171100	Clay				
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water	er well was Construe	cted reconstru	cted or nlugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, a reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 2 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No					
under the business name of 294th w. 85. th. 4/1 Well by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					