

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>MEAD</u>	<u>NE 1/4 NW 1/4 NW 1/4</u>	<u>34</u>	T <u>30</u> S	R <u>27</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?  
Go N. of Fowler 2 miles then WEST 3 miles and 1/2 mile South

2 WATER WELL OWNER: FOWLER FEEDERS monitor well  
 RR#, St. Address, Box #: 5113 23rd RD #1  
 City, State, ZIP Code: Fowler KS 67844  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>25</u> ft. ELEVATION:
--	---

1 Mile  
N  
W  
E  
S

Depth(s) Groundwater Encountered 1. 12' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 14' ft. below land surface measured on mo/day/yr 4-17-02

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 1/4 in. to 25 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		<u>10 Monitoring well</u>

Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued. Clamped. Welded. Threaded. <u>X</u>
<u>2 PVC</u>	4 ABS	7 Fiberglass		

Blank casing diameter 2" in. to 10 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>3 Mill slot .010</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 25 ft. to 10 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 8 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 8 ft. to 0" ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	<u>10 Livestock pens</u>	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? South How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0"</u>	<u>3'</u>	<u>Top Soil Brn</u>			
<u>3'</u>	<u>10'</u>	<u>Gray Caliche Shale</u>			
<u>10'</u>	<u>25'</u>	<u>Top Clay &amp; Silt</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-17-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 665 This Water Well Record was completed on (mo/day/yr) 4-25-02 under the business name of PRATT WELL ENVIRONMENTAL by (signature) Steven Egan