USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

								100	eka, K	ansas 666	20	
	County	Fract	ion			Section	number	Township number	Ran	ge numbe	er	
1. Location of well:	Meade	NW	1/4 NW	1/4 SV	1/4	36		т 30 s	R	2	7	E(W)
2. Distance and direction from nearest town or city:						3. Owner of well: Zorthan & Sons						
2 mi. west-½ north of Fowler Street address of well location if in city:												
Street address of well location it in city: City, state, zip code:								Fowler, Kansas	•			
4. Locate with "X" i	in section below:	Sketch	map:					6. Bore hole dia. 28 in				
N								Well depth 217 ft. 6-20-77				
1 !!!								7 Cable tool Rotary Driven Dug				
NW NE								Hollow rod Jetted		Bored ≥	Reverse	rotary
								8. Use: Domestic Public supply Industry				
<u>₹</u> w								X Irrigation Air conditioning Stock				
sw se								LawnOil field water Other 9. Casing: Material Height: Above or below Threaded Welded Surface in.				
								9. Casing: Material Height: Above or below				
								ThreadedWeldedSurfacein. RMPPVCWeight 31 . 66 lbs./ft.				
								Dia. 16 in. to 217ft. de	•	_		
5. Type and color of						From	То	Dia in. to ft. de				
						1		10. Screen: Manufacturer's	name _	Cook		
Surface						0	3	W.A.Brown Free				
Brown and	green clay		-			+ 3	16	Type 1.7% & 35%	Die	16	137	
	alf med. sand					16	22	Type 17% & 35% Slot/gauze 1/8 Set between 25	Len	od 32		£4
Blue clay	7					22	26	ft.	and	207		ft.
Fine to b	alf med. sand					26	32	Gravel pack? <u>yes</u> Size	ange of	material	<u> 5/80</u>	MA
Blue, brown and green clay						32	93	11. Static water level:				day/yr.
A-1 loose	med. sand and gr	ave	1			93	105	ft. below land s	urface	Date 2	- 16	12
Sandy brown clay						105	122	12. Pumping level below la	nd surfa	ices:	E00	
Half med. sand and gravel						122	128	200 ft. after5_	hrs. p	umping .	<u> </u>	g.p.m.
Sandy brown clay						128		ft. after hrs. pumping g.p.,				
	xy with 35% fine x	sand	l			140		12 W				day/yr.
Sandy brown clay						146	167	Yes X No	Date			-,, ,.
Coleche clay and sandrock						167	197	14. Well head completion:				
Good brown rock and gravel						197	208	I Titless dudpiei miches above grad				ade
Yellow cl							3222	15. Well grouted? <u>no</u>				
Blue shal	3					222	225	With: Neat cement			c	ncrete
								Depth: From ft - to		<u> </u>	H'-1	eld
								16. Nearest source of possil		taminatio	n: Fi	
								Well disinfected upon comp			e	
							-	17. Pump:		Not ins		
								Manufacturer's name				
								Model number	HF		Volts	
								Length of drop pipe	ft.	capacity	y !	3.b [·] m.
								Type: Submersible			Turbine	
70						+		Jet			Reciproc	ating
	(Use a second s	heet if	needed)					Centrifugal			Other	
18. Elevation:	19 . Remarks:							20. Water well contractor	certifi	cation:		
10 of groute and pump slab to be								This well was drilled under my jurisdiction and this report				
installed by the customer-he knows								is true to the best of my knowledge and belief. Ace-Hi International 190				
Topography: Hill Hill Hill								Business name	nat	TOUS		190
Slope	0+							Address Dodge	Cit	у, К	s.	e 140.
Upland	Zerhier fer	0_	_					Signed Coule	Zit	tel	_ Da 6	-24
X Valley	Ja Chrents or	line	<u>~</u>					Authorized r	epresen	tative	- 5018	
Forward the white, bl	ue and pink copies to the Department	of Hed	alth and Env	rironment						F	orm WWC	:-5