

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

18674

1 LOCATION OF WATER WELL: County: Meade Fraction SW 1/4 NW 1/4 SE 1/4 1/4 Section Number 25 Township No. T 30 S Range Number R 27 E W Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: 1 Mile West, 1 1/2 Mile North, 1/2 Mile West of Fowler

2 WATER WELL OWNER: Mr. Chester Rexford RR#, Street Address, Box #: 2206 9 Road City, State, ZIP Code : Montezuma, Kansas 67867 3 LOCATE WELL WITH AN "X" IN SECTION BOX: [Diagram showing section box with 'X' in SE quadrant] 4 DEPTH OF COMPLETED WELL: 295' Depth(s) Groundwater Encountered (1) 150' (2) 200' (3) 213' 255' WELL'S STATIC WATER LEVEL 49' ft. below land surface measured on mo/day/yr. 8-25-13...

5 TYPE OF CASING USED: [X] PVC [ ] Steel [ ] Other CASING JOINTS: [X] Glued [ ] Bolted [ ] Clamped [ ] Welded [ ] Threaded Casing diameter 16 in. to 2.15 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in., Weight lbs./ft., Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: [X] PVC [ ] Steel [ ] Stainless Steel [ ] Brass [ ] Galvanized Steel [ ] None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: [ ] Continuous slot [ ] Mill slot [ ] Gauze wrapped [ ] Torch cut [ ] Drilled holes [ ] None (open hole) [ ] Louvered shutter [ ] Key punched [ ] Wire wrapped [ ] Saw cut [ ] Other (specify) SCREEN-PERFORATED INTERVALS: From 2.15 ft. to 295 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 20 ft., From ft. to ft.

6 GROUT MATERIAL: [X] Neat cement [ ] Cement grout [X] Bentonite [ ] Other bentonite Grout Intervals: From 0 ft. to 16 ft., From 16 ft. to 20 ft., From ft. to ft. What is the nearest source of possible contamination: [ ] Septic tank [ ] Lateral lines [ ] Pit privy [ ] Livestock pens [ ] Insecticide storage [ ] Other (specify below) [ ] Sewer lines [ ] Cesspool [ ] Sewage lagoon [ ] Fuel storage [ ] Abandoned water well [ ] Watertight sewer lines [ ] Seepage pit [ ] Feedyard [ ] Fertilizer storage [ ] Oil well/gas well Direction from well Distance from well

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include: 0-30 Topsoil & Clay Tan, 30-45 Clay, 45-150 Clay turn Blue & soft, 150-165 Sand Fine, 165-180 Sand Fine, 180-195 Clay 3 ft. Fine Sand, 195-200 Clay, 200-206 Sand med. to coarse, 206-210 Clay & little fine sand, 210-213 Clay, 213-218 Sand med. to coarse, 218-225 Clay & Sand strips, 225-227 Sand med. to coarse, 227-232 Clay, 232-236 Sand fine, 236-240 Clay & little Fine Sand, 240-255 Sandstone tight & little clay, 255-279 Soapstone & little Sand, 279-292 Soapstone with clay, 292-300 Clay tight

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [ ] reconstructed, or [ ] plugged under my jurisdiction and was completed on (mo/day/year) 8-25-13, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 223 This Water Well Record was completed on (mo/day/year) 9-20-13 under the business name of Dunham Drilling, Inc. by (signature) K. Allen Dunham

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.