WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: COUNTY: 060 MEADE	NE 1	1/4 NE			1 32		1 1	30	S	1	R 27	W	
Distance and direction from APPROX. 1 MILES NORTH AND 5	MILES WEST	OF FOWLE		address		located		·					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP code :	POST BROTHE	RS %PHIL				loard of applicati	Agricul	ture, D	ivision 196	of Wa	ter Re		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH	OF COMPLE	ETED WELL	363								ft
\	1 1	WELL'S S			L 55 ft. Well wate								
		¦ Estimate 	d Yield	1150 gpi	m: Well wat	er was	0 f1	t. after	0	hours	pumpin	g 0	9
W ::	E :	1					70 ft.,	and	ia.	to	0 ft.		
		}							12 W				1
,	i i	i Was a cn ! If was	emicai/Da	acterioi(ogicai samp was suhmit	ile submi Ited	itted to	o departi	ment? W Wate	10 ; r well	disin	fected?	v
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI	O2 PVC 16 in. 1 Irface 12	to 368 f 2 in., L: 07 PVC	CASING t., Dia weight	 6 JOINTS	: : GLUED n. to () ft., D)ia	in, t	 o 0	ft.			
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI	02 PVC 16 in. 1 Irface 12 ON MATERIAL	to 368 f 2 in., L: 07 PVC 03 WILL	CASING t., Dia weight	6 JOINTS ii 20 II	: : GLUED n. to () ft., D I thickn	oia ness or	in. t gauge N	 o 0	ft.			
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI	02 PVC 16 in. 1 Irface 12 ON MATERIAL NGS ARE:	to 368 f 2 in., L: 07 PVC 03 WILL From 22 From From 2	CASING t., Dia weight SLOT ft. to oft. to	G JOINTS in 20 II	: GLUED n. to (bs/ft. Wal	0 ft., D 1 thickn 0 ft. 0 ft. 0 ft.	olia ness or to to	in. to gauge No	 o 0	ft.			
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 03 BENTON GROUT Intervals: From What is the nearest source	O2 PVC 16 in. f Irface 12 ON MATERIAL INGS ARE: :: :: :: :: :: :: :: :: :: :: :: :: :	to 368 f 2 in., L: 07 PVC 03 NILL From 22 From 2 From 2	CASING t., Dia weight SLOT 7 ft. to 0 ft. to 0 ft. to	367 f 0 ft.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From	0 ft., 0 1 thickn 0 ft. 0 ft. 0 ft.	olia ness or to to to to	in. to gauge No.	0 0 0616	ft.			
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI GRAVEL PACK INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? NORTH	O2 PVC 16 in. to find the second seco	to 368 f 2 in., L: 07 PVC 03 NILL From 22 From 2 From 2	CASING t., Dia weight SLOT ft. to ft. to ft. to ft. to	367 f 0 ft.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	0 ft., 0 1 thickn 0 ft. 0 ft. 0 ft.	to to to	in. to	0 0 0616	ft. Ho		feet?	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? NORTH FROM TO 0	O2 PVC 16 in. 1 Irface 12 INGS ARE: IITE Oft. to of possible AND WEST	to 368 f 2 in., L: 07 PVC 03 NILL From 22 From 2 From 2 From 2	CASING t., Dia weight SLOT ft. to ft. to ft. to ft. to	367 f 0 ft.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	Oft., D Oft. Oft. Oft. Oft.	to to to	in. to	0 0 0616	ft. Ho	r many	feet?	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI GRAVEL PACK INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? NORTH FROM TO	O2 PVC 16 in. 1 Irface 12 ON MATERIAL INGS ARE: 3: 3: IITE 0 ft. to of possible AND WEST CY CLAY 05 S E SAND 08 MG	to 368 f 2 in., L: 07 PVC 03 NILL From 22 From From 2 From 20 ft., e contamin	CASING t., Dia weight SLOT 7 ft. to 0 ft. to 0 ft. to 0 ft. to 10 ft. to	367 f 0 ft.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	Oft., D Oft. Oft. Oft. Oft.	to to to	in. to	0 0 0616	ft. Ho	r many	feet?	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source Direction from well? NORTH FROM TO 0	O2 PVC 16 in. 1 Inface 12 ON MATERIAL NGS ARE: 3: 3: IITE 0 ft. to of possible AND WEST LITE () Y CLAY 05 S E SAND 08 NO	to 368 f 2 in., L: 07 PVC 03 NILL From 22 From From 2 From 20 ft., e contamin	CASING t., Dia weight SLOT 7 ft. to 0 ft. to 0 ft. to 0 ft. to 10 ft. to	367 f 0 ft.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	Oft., D Oft. Oft. Oft. Oft.	to to to	in. to	0 0 0616	ft. Ho	r many	feet?	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? NORTH FROM TO 0	O2 PVC 16 in. to of possible and west ITTE of t. to of possible and west E SAND 08 ME OY CLAY 05 SE SAND 08 ME OY CLAY	to 368 f 2 in., L: 07 PVC 03 MILL From 22 From 20 ft., e contamin THOLOGIC L SAND EDIUM SAND	CASING t., Dia weight SLOT 7 ft. to 0 ft. to 0 ft. to 10 ft. to	367 f 0 f 370 f 0 f 4 ABAND.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	Oft., D Oft. Oft. Oft. Oft.	to to to	in. to	0 0 0616	ft. How	r many	feet?	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source Direction from weil? NORTH FROM : TO :	O2 PVC 16 in. 1 IFFACE 12 INFFACE	to 368 f 2 in., L: 07 PVC 03 MILL From 22 From 20 ft., e contamin THOLOGIC L SAND EDIUM SAND	CASING t., Dia weight SLOT 7 ft. to 0 ft. to 0 ft. to 10 ft. to	367 f 0 f 370 f 0 f 4 ABAND.	: GLUED n. to (bs/ft. Wal t., From t., From t., From t., From t., From	Oft., D Oft. Oft. Oft. Oft.	to to to	in. to	0 0 0616	ft. How	r many	feet?	

t under the business name of HENKLE DRILLING & SUPPLY by (signature)

COUNTY:	060 WEADE	·
00# C+	Addrace	POST BROTHERS %PHILLIP Box # : P.O. BOX 1150 Board of Agriculture, Division of Water Resources code : MEADE, KS 67846- Application Number: 24,196
FROM !		LITHOLOGIC LOG ;
245 † 264 †		O7 FINE SAND 08 MEDIUM SAND 09 COARSE SAND : O1 CLAY 04 SANDY CLAY 31 CALICHE
288		31 CALICHE 04 SANDY CLAY
312		23 SANDSTONE 01 CLAY
321 !		23 SANDSTONE
346		O7 FINE SAND 08 MEDIUM SAND 09 COARSE SAND
367	380	19 SHALE
	1	
i !	i	
}	;	1
1	:	
;		
;		
!	!	i I
;		
i		
;	:	
1	}	
;		
i	i	
!		
;		
;		
1	1	1
1	1	
;		
i	i	i !
!	!	
1	1	
}	1	1
	1	
1		
i !		
		·

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 10/31/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 10/31/94

under the business name of HENKLE DRILLING & SUPPLY

by (signature)

Successful my Rounder of mo/day/yr) 10/31/94

by (signature)