USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction	Section	number	Township number	Range number
l. Location of well:	Meade	SW 1/4 SW 1/4 NE	1/4 35		т 30 9	s R 28 E/W
2, Distance and dire	ction from necrest town or city: th-12 West of Mead		3. Owner of wel		die or Bill K	
		3	R.R. or street:	Μe	eade, Kansas	
orreet address of well	I location if in city:		City, state, zip			
4. Locate with "X"	in section below:	Sketch map:			6. Bore hole dia. 28_i	n. Completion date
N	١			384	Well depth	7-30-76
	!				7 Cable tool _ Rotar	y Driven Dug
NW	NE				Hollow rod Jette	Bored X Reverse rotary
<u></u>	<b>K</b>					Public supply Industry
₩					X Irrigation Air conditioning Stock Lawn Oil field water Other	
sw	SE					
					Threaded Welded	Height: Above or below Surface 10 in. Weight 31,66 lbs./ft.
	S				RMP PVC	Weight 31 . 66 _lbs./ft.
1 N	Aile <del></del> 1				Dia.15 in. to 384 ft. d	epth Wall Thickness: inches or
5. Type and color of material				То	Dia in. to ft. de	
				<del>                                     </del>	10. Screen: Manufacturer's  N.A.Brown	name
Surface				3	Type _ 10%Free_i	31 ( <b>Dig.</b> 16
Galanha alar and maal			25	25	Slot/gauze	
Coleche clay and rock Fine sand					Set between 104	
				101	Gravel pack? Yes Size	range of material CMA 3/8 do
Brown clay Half med. sand and gravel				161		
Brown clay				1	120 ft. below land	mo./day/yr. urface Date <u>7-20-76</u>
Half med. sand and gravel			161 171			
Fine sand with 30% brown clay mixed			185		_200 ft. after _2_	. hrs. pumping <u>210</u> 0g.p.m.
Med. sand			188			hrs, pumpingg.p.m.
Coleche clay			220		Estimated maximum yield —	
Med. sand and fine gravel			222		13. Water sample submitted	Date
Brown clay			259			
Med. sand and gravel			267			X Inches above grade
Blue clay			280		15. Well grouted? NO	
Blue clay with 35% blue sand			291			Bentonite Concrete
Brown clay			304			
Brown clay with 35% sand and gravel mixed				-	16. Nearest source of possi	
Brown sandy clay			326		Well disinfected upon com	
Good sand and gravel			332	4	17. Pump:	Not installed
Brown sandy clay Half med. sand			344	700	Manufacturer's name	oulds /
Half med. sand with 25% clay mixed			772		Model number 14JIIM	•
	clay and rock	Tay mixed	375 380		Length of drop pipe —————————————————————————————————	ft. capacity 1809 .p.;m.
On Teche	oray and rock			700	Submersible	X Turbine
					Jet	Reciprocating
	(Use a second	sheet if needed)			Centrifugal	Other
18. Elevation:	19. Remarks:	+ and	A - 1		20. Water well contractor	
Top 10' of grout and pump slab to be				This well was drilled under is true to the best of my kn	my jurisdiction and this report	
Topography: installed by customer-he knows this is				.5	Ace-Hi Inter	
Hill Business some						2 Dodge Cicense No.
Slope	a reguration	11.0. 11/	D		Address BOX 144	2, Dodge City, K
X Upland Valley	I 4.	VADVIAM >KA	62.		Signed Authorized	epresentative Date
	· · · · · · · · · · · · · · · · · · ·				. AUTHORIZED	epi eselliuli ve