WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No. 6412	
1 LOCATION OF WATER WELL: County: MEADE	Fraction 1/4 SE 1/4 NE 1/4 NE 1/4	Section Number Township No. Range Number 2 T 30 S R 28 □E ✓W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:			
from nearest town or intersection: If at	Latitude: (in decimal degrees)		
FROM NORTH SIDE OF MEADE- 11-1/2 M. NORTH ON HWY 23,		Longitude: (in decimal degrees)	
4,450 FT. NORTH & 135 FT. WEST		Elevation:	
2 WATER WELL OWNER: BRAD BOYD		Datum: WGS 84, NAD 83, NAD 27	
RR#, Street Address, Box #: 2119 18 ROAD		Collection Method: GPS unit (Make/Model:)	
O'4. O4.4. 7TD O-1-	E, KANSAS 67864	Digital Map/Photo, Topographic Map, Land Survey	
MEADE	E, KANSAS 07004	Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m	
3 LOCATE WELL	200		
SECTION BOX: Depth(s) Ground			
WELL'S SIAI	WELL'S STATIC WATER LEVEL165		
	Pump test data: Well water was		
NW - NE - EST. YIELD			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No			
S If yes, mo/day/yr sample was submitted			
1 mile Water well disinfected? ☐ Yes ✓ No			
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter			
Casing height above land surface12.	in. Weight 42.05	lbs./ft., Wall thickness or gauge No250	
TYPE OF SCREEN OR PERFORATION	MATERIAL:	,,,,,,,, .	
		Other (Specify)	
☐ Brass ☐ Galvanized Steel			
SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot	Gauze wrapped Torch cut	Drilled holes None (open hole)	
Louvered shutter Key punched	Wire wrapped Saw cut	Other (specify)	
SCILLIVI EIG OKATED INTERVALS.			
From			
From			
6 GROUT MATERIAL: ☐ Neat cement			
Grout Intervals: From ft. to	ft., From f	ft. to ft., From ft. to ft.	
What is the nearest source of possible conta	amination:		
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)			
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well N/A			
Direction from well		· - ·	
FROM TO LITHOLOG	***************************************	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
		<u>= 120001101112441124</u>	
		47.44	
SEE ATTACHED LO	G		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year)11-29-10 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year)			
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) . Nora Keller			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			

6412

NAME COUNTY **BRAD BOYD**

COUNT

MEADE

DATE

4-30-10

LOCATION:

NE 1/4 2-30-28

STATIC WATER LEVEL -

TEST # 1-10

0' TO 6' - SURFACE TOP SOIL BROWN CLAY

6' TO 80' - BROWN, GRAY & WHITE SANDY CLAY & CLAY

80' TO 160' - SAND WITH COARSE SAND & GRAVEL STRIPS

160' TO 180' - FINE TO MEDIUM FAIRLY LOOSE SAND WITH COARSE SAND & SMALL GRAVEL STRIPS

180' TO 220' - MEDIUM TO COARSE FAIRLY LOOSE SAND WITH GRAVEL

220' TO 240' - MEDIUM TO COARSE FAIRLY LOOSE SAND WITH BIG GRAVEL

240' TO 260' - MEDIUM TO COARSE FAIRLY LOOSE SAND

WITH GRAVEL & LITTLE CLAY MIX

260' TO 280' - FINE FAIRLY LOOSE SAND WITH CLAY MIX & SANDY CLAY STRIPS

280' TO 300' - FINE FAIRLY LOOSE SAND WITH COARSE SAND STRIPS

& CLAY MIX & BROKEN ROCK STRIP

300' TO 320' - BROKEN ROCK WITH FINE SAND & CLAY MIX

& SANDY CLAY STRIPS

320' TO 360' - FINE FAIRLY LOOSE SAND WITH CLAY MIX & SANDY CLAY STRIPS

360' TO 380' - FINE FAIRLY LOOSE SAND WITH CLAY MIX TO BROWN &

GRAY SANDY CLAY

380' TO 400' - GRAY CLAY & SHALE