

OF WATER WELL Meade	Fraction 1/4 1/4 NE 1/4	Section Number 8	Township Number T 30 S	Range Number R 29 EW
-------------------------------	--	---------------------	---------------------------	--------------------------------

Distance and direction from nearest town or city? **Meade 1 1/2 North on K-23 - 9 1/2 West - 1/2 South** Street address of well if located within city?

2 WATER WELL OWNER: **Chester Rexford**
 RR#, St. Address, Box # : **Montezuma, KS 67897**
 City, State, ZIP Code :
 Board of Agriculture, Division of Water Resources
 Application Number:


3 DEPTH OF COMPLETED WELL **439** ft. Bore Hole Diameter **26** in. to ft., and in. to ft.
 Well Water to be used as:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Observation well
 Well's static water level **Approx. 180** ft. below land surface 'measured on month day year
 Pump Test Data : Well water was ft. after hours pumping. gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing dia in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 Screen or Perforation Openings Are:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 Screen-Perforation Dia. in. to ft., Dia in. to ft., Dia in. to ft.
 Screen-Perforated Intervals: From ft. to ft., From ft. to ft., From ft. to ft.
 Gravel Pack Intervals: From ft. to ft., From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From ft. to ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
 13 Watertight sewer lines **N/A Center of Section**
 Direction from well How many feet ? Water Well Disinfected? Yes No
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample
 was submitted month day year: Pump Installed? Yes No
 If Yes: Pump Manufacturer's name Model No. HP Volts
 Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on **April** month **1** day **1981** year, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **208**
 This Water Well Record was completed on **October** month **20** day **1981** year under the business name of **Minter Wilson Drilling Co., Inc.** by (signature) *Chester Rexford*

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
			SEE ATTACHED			



ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 30
R 29
EW
SEC. 8
1/4
NE 1/4
1/4

*The
Professional*

MINTER-WILSON DRILLING CO.

INCORPORATED

1000 W.
3rd Street,
Wichita, Kansas
66202
Tel. 620-622-1111
Art. 10-1-68

WICHITA, KANSAS • P.O. BOX 411 • WASHINGTON, D.C. • WASHINGTON, D.C. • WASHINGTON, D.C. • WASHINGTON, D.C.

After the removal of the well casing and screen the open hole was back filled with chlorinated sand and gravel up to 115 feet below ground surface. The sand and gravel was immersed in a 200 mg/l chlorine solution before it was slowly placed into the open hole to prevent bridging.

From 115 feet to 65 feet below ground surface placed by tremie pipe method, a column of bentonite grout consisting of no less than 0.5 pounds of commercial sodium bentonite to 1 gallon of clean clear water which equals the 50 foot vertical column of the bore hole. This was done in one continuous operation.

From 65 feet to ground surface, the remaining hole was filled with clays, sand and gravel.