. LOCATION OF	WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sum		SW 1/4	SE 1/4 S	W 1/4	16		2177	
	tion frem nearest town or city			N 1/4		T 30 s	R 3W E/W	
Approx. 2 m. N. of town, 3/4 m. W., N. side Conway Springs, KS.								
WATER WELL OWNER: LANGE, Virginia Ryno								
RR#, ST. ADRI		W. 120th				Board of Agriculture	e, Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Conway Springs,							Application Number:	
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 50						VATION:		
AN "X" IN SEC	TION BOX:	Depth(s) groundwa	ater Encountered	1	ft.	2 ft.	3 ft.	
1 î 1		WELL'S STATIC W		FT.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	08/20/1998	
N		Pump test	data: Well w	ater was	ft. a	fter hours p		
ایا		Est. Yield	6.	ater was		ofter hours p		
	E	Bore Hole Diameter		to 50	ft.		n. to ft.	
		WELL WATER TO I		Public wate			1 Injection well 2 Other (Specify below)	
s	wsig	1 Domestic 2 Irrigation		Oil field wa		Monitoring well	2 Other (Speeny below)	
							mo/day/yr samnle was	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PVC	4 ABS		7 Fiberglass	S	DR-26		Threaded	
Blank casing D	iameter 5	in. to 30	ft., Dia	in.		ft., Dia in	. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	4 Galvanized steel	l	6 Concrete tile	9	ABS	12 None used	. •	
	PERFORATION OPE			ed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 30 ft. to 50 ft., From ft. to ft.								
				to	ft., From	ft. 1	to ft.	
GRAVEL PACK INTERVALS: from 24				ft. to 50 ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Count Intervals B. A. O. A. O.A.								
What is the nearest source of possible contamination:			ii. Fiom			ft. From ck pens 1	4 Abandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel sto	orage	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertiliz	er storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent							ne Apparent	
Direction from well? How many feet?								
FROM TO		LITHOLOGIC LOG		FROM	ТО	PLUGGING IN	ΓERVALS	
0 2	topsoil			1				
2 10	clay							
10 20 20 45	fine san			ł				
20 45 45 50	medium s	and			1 1			
3 30	BITATE							
		T-T-T-T-T-T-T-T-T-T-T-T-T-T-T-T-T-T-T-						
							· · · · · · · · · · · · · · · · · · ·	
				ļ				
				-			· · · · · · · · · · · · · · · · · · ·	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
was comple	ted on (mo/day/year)	08/20/	1998	and this re	cord is true to th	e best of my knowledge	and belief. Kansas Water	
Well Contractor's License No236								
Under the business name of ARALD								

•