L COLTION OF	WATER HELL	EDACTION	Water Well Record	d Form WWC-5	KSA 82a-1212			
	WATER WELL:	FRACTION			Section Number	Township Number	Range Number	
Sumner Distance and direction from nearest town or city street		SW 1/4		SE 1/4	34	т 30 s		
Distance and direction frem nearest town or city street address of well if located within city? 504 Church Conway Springs, Kansas								
504 Church Conway Springs, Kansas water well owner: GILGES, Harold								
RR#, ST. ADRI		Church	•			Board of Agricultur	e, Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Conway Spr			s, Kansas			Application Number:		
	'S LOCATION WITH	4 DEPTH OF COM		40	ft. EL	EVATION:		
AN "X" IN SEC	TION BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
		WELL'S STATIC W	ATER LEVEL 1	5 FT.	BELOW LAND SU	URFACE MEASURED ON mo/day/y	08/20/1998	
N	wNE	Pump test	t data: Well	water was	ft.	after hours p	umping gpm	
<u>.</u>		Est. Yield	61	water was	ft.	after hours p	umping gpm	
Mile	: 1 : 1~1	Bore Hole Diameter	12 in.	to 40	ft.		n. to ft.	
		WELL WATER TO I	BE USED AS: 3 Feedlot	5 Public water		•	11 Injection well	
	ws x X	1 Domestic	4 Industrial	6 Oil field wa		9 Dewatering 1 10 Monitoring well	2 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr san							mo/dox/vn somple was	
' -	S	submitted	riological sample si	admitted to De	-		es X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement					9 Other (Specify below) Welded			
2 PVC	4 ABS		7 Fiberglass	S	DR-26	•	Threaded	
Blank casing D	iameter 5	in. to 23	ft., Dia	in.	to	ft., Dia in	ı. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)							• /	
2 Brass 4 Galvanized steel 6 Concrete tile					9 ABS 12 None used (open hole) 2 None used (open hole) 2 None (open hole)			
I				zed wrapped	rapped			
The state of the s								
CODERN PERFORMATION AND PROPERTY AS								
SCREEN-I ER	rokation interv	ALS: from 23			ft., From			
				t. to 1. to 40	ft., Fro ft., Fro			
		from		t. to	ft., Fro			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 0 ft. to 23 ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:			7 TH.				14 Abandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy 8 Sewage lagoon		11 Fuel s	••	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				12 Toursellation stormers			16 Other (specify below)	
5 waterught sewer mies 6 Seepage pit 9 Feeuyaru								
Direction from well? East FROM TO LITHOLOGIC LOG				FROM	то	How many feet? 70 TO PLUGGING INTERVALS		
0 4	fine sar							
4 10	clay							
10 24	medium s	sand						
24 40	shale							
					_			
								
					1			
							70 10 10 10 10 10 10 10 10 10 10 10 10 10	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No23.6								
Under the business name of ARAD MEAL MELLING SELVACE LAND BY (Signature)								