	WATER WELL RE	CORD F	orm WW	'C-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION	(1887		ION NUMBER	1		RANGE NU	
Sumner Distance and direction from nearest town or city	SW 1/4 SW	1/4 SW	1/4	15	Т 30	S	R 3W	E/W
1174 N. Donald Lane (4 mi		•	ola Rd.)		Conway Sp	rings. Kans	sas	
2 WATER WELL OWNER: GGD INC.								
	0 W. 45th St. N.					Board of Agric	culture, Division of W	ater Resource
CITY, STATE: And:	ale, Kansas			CODE:		Application Num	ber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED W	/ELL: 65	ft.		ELEVATION:			
N De	pth of groundwater Encounter		ft.			ft.		ft.
	ELL'S STATIC WATER LEV			W LAND SU	IRFACE MEASU			
NW NE	Pump test da				ft. after		of pumping @	gpm
₩ W E B	Est. Yield: gpm Bore Hole Diameter 12	Well wate 2 in.	to 6	5 ft.	ft. after and	nours in.	of pumping @ to	gpm ft.
	ELL WATER TO BE USED A		10 0		and	9. Dewaterii	44 Inlan	tion well
	. Domestic 3. Feedlot	5. Public water	er supply	7. Lawn a	ind garden only	5. Dewatern	12. Other (Sp	
	2. Irrigation 4. Industria					10. Monitorin	-	aa aamala
·	Nas a chemical/bacteriological sa ibmitted	mple submitted to De	epartment?	YES Was V	NO Vater Well Disinfe		vhat mo/day/yr w	os sample O
5 TYPE OF CASING USED:	E Mesusht Isan	7 Fiberaless	9 Ot	her (Specify	below) CAS	NG JOINTS: C	Glued	Threaded
1. Steel 3. RPM (SR) Welded Clamped								
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete tile	,					
Blank casing diameter 5	in. to 25 ft.		in.	to	ft., (Dia. i	in. to	ft.
Casing height above land surface:	12 in.,	Weight: 2	2.35 lb	s. / ft.	Wall thi	ckness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENING	GS ARE:	, ,					ŕ	
1. Continuous slot 3. Mill sl		rapped	7. Tor	ch cut	9. Drille	d holes	11. None (o	pen hole)
2. Louvered shutter 4. Key p			(8. Sav		10. Othe	r (specify)	•	•
,,			65					
SCREEN - PERFORATION INTERVAL	From 25	ft. to	05	ft.,	From	ft.	to	ft.
CDAVEL BACK INTERVALS.	From 24	ft. to	65	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	110111		03	ft.,	From	ft.	to	ft.
O COOLT MATERIALS	From	ft. to	_	ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft. From ft to ft From 35 ft to 40 ft.								
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From 35 ft. to 40 What is the nearest source of possible contamination:								
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide s					cide storage	15. Oil well/G		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								ecify below)
3. Watertight sewer line 6. Seepa	ige pit 9. Feed ya	rd 12	2. Fertilizer	storage			64 - 1	
Direction from well? North	LITHOLOGIC LOC		From	To	How ma	ny feet? 50	GIC LOG	
From To 0 4 topsoil	LITHOLOGIC LOG		From	То		LITHOLO	GIC LOG	
4 15 clay								
15 32 medium coar	se sand							
32 65 shale								
			-					
					20.0			
					 -	*		
7								
Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and								
was completed on (mo/day/year) 8/23/2007 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/29/2007								
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp								