WATER WELL RECORD F	orm WWC-5 KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION		RANGE NUMBER
Sumner SW 1/4 SW 1/4 NW  Distance and direction from nearest town or city street address of well if located within city?	1/4 33 T 30 S	R 3W E/W
218 N. 6th St. Conway Springs, Kansas		
2 WATER WELL OWNER: LITTLE FOLKS CHILD CARE CEN	TER	
RR#,ST. ADDRESS,BOX #: 218 N. 6th St.		Division of Water Resource
CITY, STATE: Conway Springs, Kansas	ZIP CODE: Application Number:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 65	ft. ELEVATION:	
WITH AN "X" IN SECTION BOX:  Depth of groundwater Encountered:	ft. ft.	ft.
WELL'S STATIC WATER LEVEL 12	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr:	6/9/10
Pump test data: Well water		
Est. Yield: gpm Well water Bore Hole Diameter 12 in.		
Bore Hole Diameter 12 in.  WELL WATER TO BE USED AS:	to <b>65</b> ft. and in.	to ft.
	er supply 7. Lawn and garden only 9. Dewatering	11. Injection well Other (Specify below)
	ter supply 8. Air conditioning 10. Monitoring well	
S Was a chemical/bacteriological sample submitted to Di submitted	epartment? YES NO ; If yes, what mo	o/day/yr was sample NO
5 TYPE OF CASING USED:		
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	Malda.	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tild		Johnson
Blank casing diameter 5 in. to 25 ft., Dia.	in. to ft., Dia. in.	to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft. Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL:		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
1. Continuous slot 3. Mill slot 5. Gauzed wrapped		. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 25 ft. to	65 ft., From ft.	to ft.
From ft. to	ft., From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	65 ft., From ft.	to ft.
From ft. to	ft., From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug		
Grout Intervals: From 4 ft. to 24 ft., From	ft. to ft., From ft.	to ft.
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy	Livestock pens 13. Insecticide storage 15. (	Oil well/Gas well
. Copilo Link	. Fuel storage 14. Abandon water well 16. 0	Other (specify below)
	2. Fertilizer storage	
Direction from well? West	How many feet? 10 ft. plus	s
From To LITHOLOGIC LOG	From To LITHOLOGIC L	_OG
0 4 sandy soil		
4 10 clay 10 65 red shale		
U US HEU SHAIC		
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed or 3. plugged under my	y jurisdiction and
(10/2010	2. reconstructed or 3. plugged under my true to the best of my knowledge and belief.	y jurisdiction and
was completed on (mo/day/year) 6/9/2010 and this record is	true to the best of my knowledge and belief.	y jurisdiction and
was completed on (mo/day/year) 6/9/2010 and this record is		