USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number		
1. Location of well:	MEADE	NV1/4 SE 1/4NW	1/4	13		т 30 s	R 30	≠ /w	
	ction from nearest town or city: s re 2 south s east $\frac{1}{4}$	outh of Copelan south	R.R. or s	treet:	Me	erry Grace eade, Ks. 67864			
City, state, zip code: 4. Locate with "X" in section below: N						6. Bore hole dia. 26 in. Well depth 131 ft.		-30- 76	
₩ NE E						7Cable toolRotary Driven Dug Hollow rod Jetted BoredX Reverse rotary 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other			
sw 			·····			9. Casing: Material stool Threaded Welded _x RMP PVC Dia. 16 in. to 132ft. dept	Height: Above or bel Surface 12 Weight 36 86	ow in.	
5. Type and color of material				From	То	Diain. toft. depth gage No 10. Screen: Manufacturer's name Johnson Division			
						Type Galv. Slot/gauze 100 Set between 100 Perf. 190-100t. a	Dia. <u>16"</u> Length <u>20"</u> ft. and <u>120</u>	ft.	
						Gravel pack 26 Size ran 11. Static water 88: - 20 ft. below land surf	nge of material 111	Іау/ут.	
						12] Sumping level below land ft. after h	surfaces: 1600	.p.m.	
						13. Water sample submitted:	.600 mo./d	i.p.m. i.p.m. lay/yr.	
					_	14. Well head completion: Pitless adapter		nde	
				•		15. Well grouted? Yes With: Neat_cement Depth: From ft. to _	Bentonite Co	ncrete /A	
						16. Nearest source of possible ft Direction Well disinfected upon complete	Туре	No	
						17. Pump: Groum Manufacturer's name Model numberJHC	HP 200 Volts	S 7	
						Length of drop pipe 240 Type: Submersible	ft. capacity	<u> </u>	
	(Use a second si	neet if needed)				Jet Centrifugal	Reciproce	iting	
18. Elevation: Topography: Hill Slope	19. Remarks:					20. Water well contractor's of This well was drilled under my is true to the best of my knowl Minter Wilson Business name 0. Box Address	ivrisdiction and this re ledge and belief.	port 8	
Upland Valley Forward the white, blu	e and pink copies to the Department	of Health and Environment	·			Authorized repr	esentative Date	<u>-</u>	

Professionals MINTER-WILSON DRILLING CO. Complete installation and Repairing

Phone 276-8269 . P.O. Box 493 . GARDEN CITY, KANSAS 67846

JERKY GRACE Meade County 2-2-76

Location No 13-30-30 From Chester Rexfords house, 3 Ma. lest, & Mile South, East Side Of Road Static Vater Level 170*

Test #1

Ò	3	Top Soil
3	5	Brown Clay
5	50	Brown Sandy Clay
50	30	Brown Sandy Clay & Fine Sand Mixture (50%)
80	108	Fine To Med. Sand & Gravel (Lôose)
108	140	Fine To Sed. Sand & Gravel, Streaks of Clay (10%)
140	200	Fine to Ted. and & Oravel (Loose)
200	415	Fine Powed. Sand & Oravel, Streaks Of Clay (18%)
215	276	rine To med. Hand & Gravel (Loose)
276	290	Blue Clay & Brown Clay'
2 36	431	fine To hed. Land & Gravel (loose)
431	4 5 0	Brown Clay, Gray Clay, Small Streaks Of White Rock
450	455	Gray Clay (Tight)

T.D. 431'
20' Screen