WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County Meade	Fraction SE1/4NE 1/4NE 1/4		number 6	Township number 30	Range number 30	E/N
2. Distance and dire	ection from nearest town or city: 4	south, 3 east 3.	Owner of wel	ı. Tho	mas Gibson		-P
Street address of we	Il location if in city: and 3 s	outh of Copeland R.F	R. or street:	code: Co	peland, Kansas	67837	
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 26 in. Completion date 3-14-77		
1	N				Well depth _380 ft.		
					7Cable toolRotaryDrivenDugHollow rodJettedBored X Reverse rotary		
NW NE					8. Use: Domestic F		
<u></u> w					X Irrigation Air conditioning Stock		
_					Lawn Oil field water Other		
					9. Casing: Material steel Height: Above or below Threaded Welded Surface in.		
S					RMPPVCWeightIbs./ft.		
ı→ 1 Mile				1 _	Dia in. to ft. de Dia in. to ft. de	pth Wall Thickness: in	aches or
5. Type and color of material			From	То			
m	8				10. Screen: Manufacturer's		
Clay & fine sand			15	15 74	Type Bridge Slot/gauze Slot-2	Dia. 16"	100
Lime Hard Sand, clay & little lime			祝	ウェ	Set between <u>280</u>	_ft. and38	0ft.
			105	105	ft. Gravel pack? ves Size re	and	/8ft.
Sand, little cemented sand & little clay Clay & little lime					11. Static water level:		./day/yr.
Clay & little lime			130 168	154	165 ft. below land su		.,, ,
Clay, little lime & little fine sand sand & little cemented sand			175	175 189	12. Pumping level below lar		
Clay			189	191	180 ft. after		
Very hard Lime Sand			191 192	192 193	Estimated maximum yieldg.p.m.		
Clay & little lime			193	210	13. Water sample submitted:	_	./day/yr.
Clay, blue Sand & clay			210 236	236 240	Yes No 14. Well head completion:	Date	
nard Lime			1240	241	Pitless adapter	12 [#] Inches above	grade
Clay blue Sand			241 243	243 287	15. Well grouted?yes	·-	Concrete
Glay, blue			287	306	With: Weat cement		
Clay & little fine sand			306	315	16. Nearest source of possib		ne
Sand & clay little fine			31.5 321	321	ft Direction	Туре	
Sand			345	360	Well disinfected upon compl 17. Pump:		No
Fine sand Clay. lit	. & clay tle lime hard and	little sand	360 380	380 390	Manufacturer's name	elLine * La	yne "
Sand			390 394	394	Model number		_
Lime hard			1	400	Length of drop pipe — 26 Type:	ft. capacity	_g.p.m. (
sand & cl	ay	- AUT-334FD/	400	405	Submersible	Turbine	! \$
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(Use a second	sheet if needed)			Jet Centrifugal	Recipro	ocating S
18. Elevation:	19: Remarks:	- · · · · · · · · · · · · · · · · · · ·	<u>l</u>	·	20. Water well contractor's		" N
					This well was drilled under my jurisdiction and this report		
Topography:					is true to the best of my knowledge and belief. DUNHAM Drilling 223		
Hill					Business name	A Lic	23 Ense No.
X Slope					Address COFLA	y Ks	<u> </u>
Upland Valley					Signed Authorized re	presentative Date	6-24-77 L
	lue and pink copies to the Departmen	at Harlth and England				Form WW	- f