, W										
WWZ A ZIPITZIJE	D WK/K/	r pro	CODD	Form W/	WC F	ъ.	· · · CXX	D 4 3	19,298 19,299	
WATER		i	and the second s	Form WWC-5			vision of Wate on Number	er Resources App. No. Township No.	Range Number	
1 LOCATION OF WATER WELL: County: HASKELL			IER WELL:	1/4 SW 1/4 NW	' ¼ NE ½		36	T 30 S	R 31 DE W	
			f Well Location; i	f unknown, distance &			l Positioning	g System (GPS) i		
				owner's address, check		Latiti	Latitude: (in decimal degrees)			
SOUTHEAST CORNER OF SUBLETTE-10 M. E., 6 M. S.,							Longitude: (in decimal degrees)			
4,200 FT. NORTH & 2,485 FT. WEST							Elevation:			
2 WATER WELL OWNER: COLLINGWOOD TRUST							Collection Method:			
RR#, Street Address, Box #: C/O BILL ENGLER, PO BOX 1184							GPS unit (Make/Model:)			
City,	State, Z	IP Code	: HUTCH	INSON, KANSAS 67	Digital Map/Photo, Topographic Map, Land Survey					
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m										
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 440 ft.										
SECT	SECTION BOX: Depth(s) Groundwater Encountered (1)									
	N WELL'S STATIC WATER LEVEL 286									
	Pump test data: Well water wasft. after									
W -NW - NE - E EST. YIELD										
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well										
sw	Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
"	☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well									
L	Was a chemical/bacteriological sample submitted to Department? Yes V No									
	S If yes, mo/day/yr sample was submitted									
water wer districted? Tes W no										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 16 in. to 330 ft., Diameter in. to ft., Diameter ft., Diameter ft., Diameter ft.										
Casing height above land surface. 12 in., Weight .42.05 lbs./ft., Wall thickness or gauge No259										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
Steel Stainless Steel PVC Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)										
SCREE	SCREEN-PERFORATED INTERVALS: From									
	From ft. to ft., From ft. to ft. to									
GRAVEL PACK INTERVALS: From 20 ft. to 245 ft., From 305 ft. to 440 From ft. to ft., From ft. to										
6 CROI	IIT MA'	TERIAL		ent Cement grout						
Grout Int		From	0 ft. to	20 ft. From	245	ft. to .3	05 ft	From	ft. to ft.	
Grout Intervals: From 0 ft. to 20 ft., From 245 ft. to 305 ft., From ft. to ft. What is the nearest source of possible contamination:										
	Septic ta				Livestock		Insecticide	e storage O	ther (specify below)	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well										
Direc:	waterng tion from	ni sewer ii n well S	SOUTHWEST	nt reedyard [On wen/g	as wen		
FROM	TO	ii weii	LITHOLOG	IC LOG	FROM	TO			UGGING INTERVALS	
	SEE ATTACHED LOG									
			·		ļ				MINTER CONTROL	
				and the state of the property of the state o						
								·		
7 CONT	RACT	יט פישט	RIANDOWNER	2'S CERTIFICATIO	N. This wa	ter well v	was 7 const	ructed D reconst	ructed or Diblogged	

under my jurisdiction and was completed on (mo/day/year) ...3-15-12 ... and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. .. 208 ... This Water Well Record was completed on (mo/day/year) .3-16-12 ... under the business name of ... MINTER-WILSON DRILLING CO., INC. ... by (signature) ... by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to W ATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.

Check: White Copy, Blue Copy, Pink Copy

The Irrigation and Domestic Water Systems Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Repairing

INCORPORATED

Phone 620-276-8269 GARDEN CITY, KANSAS 67846 P.O. Box A •

NAME

EDNA COLLINGWOOD TRUST

COUNTY

HASKELL

DATE

12-15-11

LOCATION:

NE 1/4 36-30-31- COPELAND - 4 MILES SOUTH, 1 MILE WEST.

5 MILES SOUTH, 1/2 MILE EAST &

1/4 MILE SOUTH

STATIC WATER LEVEL - APPROX, 270 FT.

TEST#1

0' TO 45' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

45' TO 49' - FINE TO MEDIUM SAND

49' TO 60' - CEMENTED SAND

60' TO 75' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

75' TO 95' - GREEN CLAY WITH LAYERS OF BROWN SANDY CLAY

95' TO 110' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

110' TO 120' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

120' TO 128' - BROWN SANDY CLAY

128' TO 162' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

162' TO 172' - BROWN SANDY CLAY

172' TO 182' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

182' TO 195' - BROWN YELLOW CLAY

195' TO 218' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

218' TO 225' - BROWN SANDY CLAY

225' TO 246' - FINE TO MEDIUM SAND & GRAVEL

246' TO 255' - BROWN SANDY CLAY

255' TO 293' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 15%

293' TO 298' - BROWN SANDY CLAY

298' TO 321' - FINE TO MEDIUM SAND & GRAVEL

321' TO 342' - BROWN & BLUE CLAY

342' TO 374' - FINE TO MEDIUM SAND & GRAVEL

374' TO 380' - BROWN & BLUE CLAY

380' TO 393' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 30%

393' TO 400' - BROWN SANDY CLAY

400' TO 408' - FINE TO MEDIUM SAND & GRAVEL

408' TO 425' - FINE TO MEDIUM SAND & GRAVEL

AND BROWN SANDY CLAY MIXED - DRILLED TIGHT

425' TO 440' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

440' TO 495' - BROWN CLAY WITH STRIPS OF WHITE ROCK

495' TO 500' - YELLOW SANDY CLAY

500' TO 510' - BROWN CLAY

510' TO 534' - BROWN CLAY WITH LAYERS OF SAND STONE - 25%

534' TO 545' - RED BED - 250 PULL DOWN