WAIER WELL REC	JUKD	roriii vv	VV C-3			Resources App. No		
1 LOCATION OF WA County: HASKELL	TER WELL:	Fraction 1/4 SE 1/4 NE	1/4 SW 1/4		n Number 10	Township No. T 30 S	Range Number R 31 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
SE CORNER OF SUBLETTE-7 M E TO ROAD V V, 2 M S, 1 M E, 1,432 FT. NORTH & 2,693 FT. WEST					Elevation:			
					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: FRY FAMILY FARMS RR#, Street Address, Box #: ED BANNING, PO BOX 1013				Collection Method: GPS unit (Make/Model:)				
City, State, ZIP Code : GARDEN CITY, KANSAS 67846				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m								
WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	լ 410		ft.			
SECTION BOX: N	Depth(s) Groundwater Encountered (1)							
Pump test data: Well water wasft. after hours pumping gpm								
EST. YIELDgpm. Well water wasft. after hours pumping gpm								
W E Bore Hole Diameter .39in. to419ft., andin. toft.								
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well SW X SE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)								
Sw - 1 - 38 - 1								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter16 in. to330 ft., Diameter ft., Diameter ft., Diameter ft.								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 0 ft. to 20 ft., From 255 ft. to 315 ft., From ft. to ft. What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direction from well								
FROM TO	LITHOLOG	SIC LOG	FROM	ТО	LITHO. LO	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
SEE A	TTACHED LOG							
- COMMIN CONTRACTOR		NO CERMINICA MIC	N. TIL:		- D1 ·			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .11-20-14 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No								
under the business name	of MINTER-W	ILSON DRILLING C	OINC	by (si	gnature)	wa Keller		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Se								

http://www.kdheks.gov/waterwell/index.html

19,315

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

P.O. Box A • GARDEN CITY, KANSAS 67846 Phone 620-276-8269

NAME

FRY FAMILY FARMS

COUNTY

HASKELL

DATE

10-14-14

LOCATION:

SW 1/4 10-30-31 - FROM SE CORNER OF SUBLETTE - 7 MILES EAST TO ROAD V V

& 1-3/4 MILES SOUTH

1/2 OF A MILE EAST OF EXISTING WELL

STATIC WATER LEVEL -

TEST #5

0' TO 2' - TOP SOIL

2' TO 65' - BROWN CLAY & BROWN SANDY CLAY

65' TO 78' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

78' TO 100' - BROWN CLAY

100' TO 170' - BROWN CLAY WITH GRAVEL STREAKS

170' TO 230' - FINE TO MEDIUM SAND & FINE GRAVEL

230' TO 310' - FINE TO MEDIUM SAND & GRAVEL

310' TO 329' - BROWN CLAY

329' TO 384' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

384' TO 395' - BROWN CLAY WITH WHITE ROCK MIXED

395' TO 438' - BROWN SANDY CLAY

438' TO 444' - BROWN CLAY

444' TO 463' - BROWN YELLOW CLAY

463' TO 470' - SHALE