

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Haskell	S1/2 SW 1/4 SE 1/4	30	T 30 S	R 31 EW

Distance and direction from nearest town or city street address of well if located within city?

6 Miles East, 4 miles South, 1/4 Mile East

2 WATER WELL OWNER:	Mark Fincham	Murfin Drilling
RR#, St. Address, Box # :	307 S. Pursley	Box 661
City, State, ZIP Code :	Sublette, Ks. 67877	Colby, Ks. 67701
		Board of Agriculture, Division of Water Resources
		Application Number: 940370

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 330 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 8 in. to 330 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes, No, X If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
2 PVC	4 ABS		Threaded
Blank casing diameter 4.5 in. to ft. Dia	7 Fiberglass		
Casing height above land surface 4.5 in. weight 2.38 lbs./ft. Wall thickness or gauge No. 248			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 270 ft. to 330 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 330 ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 0 ft. to 20 ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? SW				
How many feet? 100'				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	13	Loess			
13	28	Clay			
28	76	Sandy Clay w/Caliche & Some Sand			
76	88	Med. Sand & Gravel			
88	96	Sandy Clay & Caliche w/some Sand Strks.			
96	276	Med. Sand & Gravel w/a few Clay & Caliche Strks.			
276	281	Sandy Clay w/some Sand Strks.			
281	327	Med. Sand & Gravel w/ a few Caliche & Clay Strks.			
327	330	Blue Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-94 and this record is true to the best of my knowledge and belief, Kansas
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 9-30-94
under the business name of Woofter Pump & Well, Inc. by (signature) <i>[Signature]</i>

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Haskell		S1/2 SW 1/4 SE 1/4	30	T 30 S	R 31 EW
Distance and direction from nearest town or city street address of well if located within city? 6 Miles East, 4 miles South, 1/4 Mile East					
2 WATER WELL OWNER:		Murfin Drilling		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		Box 661		Application Number: 940370	
City, State, ZIP Code :		Sublette, Ks. 67877 Colby, Ks. 67701			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 330 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 330 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile	
1 Steel		3 RMP (SR)		6 Asbestos-Cement	
2 PVC		4 ABS		9 Other (specify below)	
		7 Fiberglass		CASING JOINTS: Glued X Clamped	
Blank casing diameter 4.5 in. to 270 ft., Dia				Welded	
Casing height above land surface 4.5 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248				Threaded	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement	
1 Steel		3 Stainless steel		8 RMP (SR)	
2 Brass		4 Galvanized steel		9 ABS	
		5 Fiberglass		11 Other (specify)	
		6 Concrete tile		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		9 Drilled holes	
2 Louvered shutter		7 Torch cut		10 Other (specify)	
3 Mill slot				11 None (open hole)	
4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 270 ft. to 330 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From 20 ft. to 330 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout	
Grout Intervals: From 0 ft. to 20 ft.		3 Bentonite		4 Other	
				From ft. to ft.	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well	
1 Septic tank		4 Lateral lines		11 Fuel storage	
2 Sewer lines		5 Cess pool		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		13 Insecticide storage	
		7 Pit privy		15 Oil well/Gas well	
		8 Sewage lagoon		16 Other (specify below)	
		9 Feedyard			
Direction from well? SW		How many feet? 100'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	13	Loess			
13	28	Clay			
28	76	Sandy Clay w/Caliche & Some Sand			
76	88	Med. Sand & Gravel			
88	96	Sandy Clay & Caliche w/some Sand Strks.			
96	276	Med. Sand & Gravel w/a few Clay & Caliche Strks.			
276	281	Sandy Clay w/some Sand Strks.			
281	327	Med. Sand & Gravel w/ a few Caliche & Clay Strks.			
327	330	Blue Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 9-30-94 under the business name of Woofter Pump & Well, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					