WATER WELL RECORD	Form WWC-5	Division of Water	r Resources App. N	18,956				
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number				
County: HASKELL	1/4 NW 1/4 SE 1/4 SE 1/4	28	T 30 S	R 32 □E [7]W				
Street/Rural Address of Well Location;	if unknown, distance & direction	Global Positioning	System (GPS) in	nformation:				
from nearest town or intersection: If at o	Latitude: (in decimal degrees)							
SE CORNER OF SUBLETTE-5 MILES SOUTH, 1 MILE EAST,		Longitude: (in decimal degrees)						
1,165 FT. NORTH & 1,100 FT. WES		Elevation:						
	<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27							
2 WATER WELL OWNER: JOHNNY P. & MARIA B. BERG RR#, Street Address, Box #: P O BOX 312		Collection Method: GPS unit (Make/Model:)						
C'A CA ZID CA I		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey						
SUBLE	TTE, KS 67877	Est. Accuracy:	3 m. \square 3-5 m. \square	5-15 m $\square > 15$ m				
3 LOCATE WELL		Dan Treeding.	5 m, _ 5 5 m, _	5 15 m, 15 m				
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 500							
SECTION BOX: Depth(s) Ground	dwater Encountered (1)	ft. (2)	ft. (3) ft.				
N WELL'S STATI	Iwater Encountered (1)	below land surface n	neasured on mo/d	ay/yr7-7-10				
	test data: Well water was							
	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm							
W E Bore Hole Diam	W E Bore Hole Diameter30 in. toft., and in. to							
1 1 ' 1 ' 1 1	TO BE USED AS: Public water			njection well				
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
I I I I I I I I I I I I I I I I I I I	☐ Industrial ☐ Domestic-law							
	bacteriological sample submitted to		Yes 🗹 No					
	day/yr sample was submitted							
Water well disin	fected? Yes 🔽 No							
5 TYPE OF CASING USED: Steel	PVC Other							
CASING JOINTS: Glued Clan	nped 🗹 Welded 🖂 Threaded							
Casing diameter 16 in to 350	ft., Diameter in. t	o ft., Di	iameter	in. to ft.				
Casing height above land surface12.	in., Weight 42.05	lbs./ft., Wall thic	kness or gauge N	o250				
TYPE OF SCREEN OR PERFORATION	MATERIAL:							
☑ Steel ☐ Stainless Steel	□ PVC □	Other (Specify)						
	☐ None used (open hole)							
SCREEN OR PERFORATION OPENING								
Continuous slot Mill slot			☐ None (open hol					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 350 ft. to 500 ft., From ft. to ft.								
	From ft. to							
GRAVEL PACK INTERVALS:	From 20 ft to 500	ft From	ft	to ft				
	From ft. to							
6 GROUT MATERIAL: Neat ceme	ent Cement grout Benton	ite						
6 GROUT MATERIAL: Neat ceme Grout Intervals: From0 ft. to	20 ft From	t to ft	From	ft to ft				
What is the nearest source of possible conta			110111	. 10. 00				
	nes Pit privy Livestock p	ens 🗌 Insecticide	storage Oth	er (specify below)				
☐ Sewer lines ☐ Cesspool	☐ Sewage lagoon ☐ Fuel storage		water well	(
☐ Watertight sewer lines ☐ Seepage p								
Direction from well	Distance f	rom well						
FROM TO LITHOLOG	IC LOG FROM	TO LITHO. LC	OG (cont.) <u>or</u> PLU	IGGING INTERVALS				
SEE ATTACHED LOC	3							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year)7-22-10 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)7-27-10								
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mora Heller								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								

Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Domestic and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

JOHNNY BERG

COUNTY

HASKELL

DATE

3-17-10

LOCATION: SE 1/4 28-30-32 - FROM SE CORNER OF SUBLETTE - 5 MILES SOUTH

& 1/2 MILÉ EAST ON THE NORTH SIDE

- 1,874 FT. NORTHEAST OF EXISTING WELL

STATIC WATER LEVEL - APPROX. 310 FT.

TEST #1

a. = a	401	 	O1 4 1 /
	10' - TOP		

10' TO 15' - WHITE SANDY CLAY

32' - BROWN SANDY CLAY - LITTLE CALICHE 15' TO

51' - SAND MEDIUM - SANDY CLAY - 10% 32' TO

80' - BROWN CLAY 51' TO

85' - BROWN SANDY CLAY 80' TO

85' TO 89' - GRAY SANDY CLAY

89' TO 109' - BROWN SANDY CLAY

109' TO 114' - SAND FINE TO MEDIUM

114' TO 141' - SAND MEDIUM TO COARSE - LITTLE GRAVEL

141' TO 147' - SANDY CLAY

147' TO 169' - SAND MEDIUM TO COARSE

169' TO 171' - CLAY

171' TO 184' - SAND MEDIUM TO COARSE - LITTLE GRAVEL

184' TO 189' - SANDY CLAY

189' TO 234' - SAND MEDIUM TO COARSE - LITTLE GRAVEL

234' TO 239' - CLAY

239' TO 249' - SAND MEDIUM TO COARSE

249' TO 260' - BROWN CLAY

260' TO 262' - CALICHE

262' TO 264' - CLAY

264' TO 288' - SAND MEDIUM - CLAY 5%

288' TO 290' - CALICHE & CLAY

290' TO 320' - SAND MEDIUM TO COARSE - CLAY 1%

320' TO 380' - SAND MEDIUM TO COARSE

380' TO 400' - SAND MEDIUM TO COARSE - CLAY 8%

400' TO 420' - SAND MEDIUM TO COARSE

420' TO 425' - SANDY CLAY

425' TO 438' - SAND MEDIUM TO COARSE - CLAY 8%

438' TO 455' - YELLOW CLAY

455' TO 470' - YELLOW SANDY CLAY- LITTLE SAND

470' TO 487' - SAND FINE - SANDY CLAY 15%

487' TO 500' - YELLOW CLAY

500' TO 515' - BLUE & YELLOW CLAY

515' TO 530' - BLUE CLAY - 5' SANDSTONE

530' TO 550' - SHALE - HARD