COUNTY: 041 HASKELL	Fraction SE 1/4 SW	1/4 SE 1	Section 1/4   07	Number	¦ Township ¦ T 30	Number S	¦ Range ¦ R 33	
Distance and direction from APPROX. 3/4 MILES EAST OF S	nearest town or c	•			•			
WATER WELL OWNER: RR#, St. Address, Box # :	DENNIS BLACK			oard of Agri				
City, State, ZIP code :	SATANTA, KS 67	7870-	Α,	oplication N				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	; 4 DEPT ; Dept		ED WELL 420 ater Encountered					
\	; ; ; ;		R LEVEL 292 ft. tdata: Well water				no/day/yr s pumping	
, , , , , , , , , , , , , , , , , , ,		nted Yield	gpm: Well wate	er was	ft. after	hour	s pumping	gp
W	E ; Bore H	dole Diameter	10 in.	to 420 ft	., and	in. to	ft.	
; S#; SE		IATER TO BE US	SED AS: <b>01 DOMEST</b>	IC				
•	: : Was a	chemical/bact , mo/day/yr s	teriological samp: sample was submit	le submitted ted	to departm	ent? <b>No ;</b> Water we	ell disinf	ected? <b>Ye</b>
Blank casing diameter Casing height above land su	5 in. to 420 rface 12 in.,	) ft., Dia weight	in. to					
Blank casing diameter Casing height above land su	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV	) ft., Dia weight C	in. to	l thickness	or gauge No	265		
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI	oft., Dia weight CC LL SLOT 310 ft. to	in. to 3 lbs/ft. Wall	l thickness	or gauge No	265		
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENIO	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI	oft., Dia weight CC LL SLOT 310 ft. to 380 ft. to	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From	thickness  ft. to  ft. to	or gauge No	265		
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft.	weight C LL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From	ft. to	or gauge No  ft. ft. ft.	265		
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL  03 BENTON	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft.	weight C LL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft.	265		
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source of Direction from well?  FROM ; TO ;	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft. of possible contam	weight  C LL SLOT  310 ft. to 380 ft. to 20 ft. to ft. to	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265		eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENION  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source of Direction from well?  FROM : TO : : 3 : 01 CLAY	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft. of possible contam	weight  C LL SLOT  310 ft. to 380 ft. to 20 ft. to ft. to	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From ft. to ft	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source of Direction from well?  FROM : TO :	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From ITE ft. to 20 ft. of possible contam LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA	oft., Dia weight C LL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ., From mination: NONE	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From ft. to ft	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source of the company of the co	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From Trom  ITE ft. to 20 ft. of possible contam  LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA	oft., Dia weight C LL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ., From mination: NONE	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From 420 ft., From ft., From ft. to ft	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENII  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source of the second of	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From Trom  ITE ft. to 20 ft. of possible contam  LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA	weight CLL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ., From sination: NONE	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From ft., From ft., From ft. to ft  COBSERVED  FROM	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENION  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source of the second se	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft. of possible contam LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA GRAVEL Y CLAY SAND 08 MEDIUM SA Y CLAY	oft., Dia weight CLL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ., From mination: NONE CLOG	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From ft., From ft., From ft. to ft  COBSERVED  FROM	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENION  SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source of the second se	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft. of possible contam  LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA GRAVEL Y CLAY SAND 08 MEDIUM SA Y CLAY UM SAND 14 MED GRA	oft., Dia weight CLL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ., From mination: NONE CLOG	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From ft., From ft., From ft. to ft  COBSERVED  FROM	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?
TYPE OF SCREEN OR PERFORATION OPENIIS SCREEN OR PERFORATION OPENIIS SCREEN PERFORATED INTERVALS  GRAVEL PACK INTERVALS  GRAVEL PACK INTERVALS  GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source of Direction from well?  FROM : TO : 3 : 01 CLAY 3 : 70 : 04 SAND 70 : 90 : 07 FINE 90 : 94 : 15 CRS 694 : 113 : 04 SAND 113 : 120 : 07 FINE 120 : 125 : 04 SAND 125 : 230 : 08 MEDIO 230 : 245 : 04 SAND 125 : 230 : 08 MEDIO 230 : 245 : 04 SAND 125 : 230 : 08 MEDIO 230 : 245 : 04 SAND 130 : 245 : 04 SAND 125 : 230 : 245 : 2	5 in. to 420 rface 12 in., ON MATERIAL: 07 PV NGS ARE: 03 MI : From From From From ITE ft. to 20 ft. of possible contam  LITHOLOGIC Y CLAY 05 SAND SAND 08 MEDIUM SA GRAVEL Y CLAY SAND 08 MEDIUM SA Y CLAY UM SAND 14 MED GRA	oft., Dia weight C LL SLOT 310 ft. to 380 ft. to 20 ft. to ft. to ft. to contains NONE CLO6 AND 11 GRAVEL AND 09 COARSE EVEL 01 CLAY	in. to 3 lbs/ft. Wall 350 ft., From 420 ft., From ft., From ft. to ff E OBSERVED  FROM	ft. to ft. to ft. to ft. to	or gauge No ft. ft. ft. ft. ft.	265	low many f	eet?

completed on (mo/day/year) 06/07/91 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 145
Under the business name of HENKLE DRILLING & SUPPLY

by (signature)

| Section Number 1 LOCATION OF WATER WELL: : Fraction ; Township Number ¦ Range Number COUNTY: 041 HASKELL : SE 1/4 SW 1/4 SE 1/4 ; 07 † T 30 S ; R 33 2 WATER WELL OWNER: DENNIS BLACK RR#, St. Address, Box # : RT. 1, BOX 121 A Board of Agriculture, Division of Water Resources City, State, ZIP code : SATANTA, KS 67870-Application Number: FROM : TO : LITHOLOGIC LOG 272 ; 281 | 01 CLAY 281 : 320 : 07 FINE SAND 08 MEDIUM SAND 35 CLAY & GRAVL 320 : 350 : 04 SANDY CLAY 05 SAND 350 : 360 : 01 CLAY 360 : 378 : 04 SANDY CLAY 05 SAND 20 LIMESTONE 378 395 ; 07 FINE SAND 08 MEDIUM SAND 09 COARSE SAND 413 : 20 LIMESTONE 01 CLAY 23 SANDSTONE 395 ; 413 442 : 19 SHALE 442 : 450 : 19 SHALE

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 06/07/91 and this record is true to the best of my knowledge and belief. Kansas This Water Well Record was completed on (mo/day/yr) 06/20/91 Water Well Contractor's License No. 145 under the business name of HENKLE DRILLING & SUPPLY