

1 LOCATION OF WATER WELL: County: Hasbrell Fraction: SW 1/4 NE 1/4 SW 1/4 Section Number: 8 Township Number: T 30 S Range Number: R 33 EW

Distance and direction from nearest town or city street address of well if located within city?

1 m E Satanta

2 WATER WELL OWNER: Amoro Production Elizabet A. Coy #4
RR#, St. Address, Box #: 530 S Grant Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Ulysses, Ks. 67880 Application Number: 183-310

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 360 ft. ELEVATION: 280 ft.

Depth(s) Groundwater Encountered 1. 280 ft. 2. 280 ft. 3. 280 ft.
WELL'S STATIC WATER LEVEL 280 ft. below land surface measured on mo/day/yr 7-25-83
Pump test data: Well water was 2 ft. after 2 hours pumping 60 gpm
Est. Yield 60 gpm: Well water was 2 ft. after 2 hours pumping 60 gpm
Bore Hole Diameter 9 in. to 9 ft., and 9 in. to 9 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes 0 No 0 If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes 0 No 0

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 0 Clamped 0
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 0
Blank casing diameter 5 in. to 9-280 ft. Dia. 5 in. to 9-280 ft. Dia. 5 in. to 9-280 ft. Dia. 5 in. to 9-280 ft. Dia.
Casing height above land surface 14 in. weight 200 lbs./ft. Wall thickness or gauge No. 0.265
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 0
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 0

SCREEN-PERFORATED INTERVALS: From 280 ft. to 360 ft. From 280 ft. to 360 ft.
GRAVEL PACK INTERVALS: From 230 ft. to 360 ft. From 230 ft. to 360 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0
Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? East How many feet? 200

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 240 overburden 01 01 overburden
240 260 coarse sand 09 09 coarse sand
260 280 " " & clay sh 04 04 " " & clay sh
280 300 coarse sand 09 09 coarse sand
300 320 med sand & clay 04 04 med sand & clay
320 340 " " " " 04 04 " " " "
340 360 med sand 08 08 med sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-25-83 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 7-25-83
under the business name of T & W Water Well Service by (signature) [Signature]
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

30

R

33

EW

SEC.

8

SW 1/4

NE 1/4

SW 1/4