

| | | | | | |
|--|--|----------------------|--|-----------------|----------------|
| 1 LOCATION OF WATER WELL | | Fraction | Section Number | Township Number | Range Number |
| County: Haskell | | SE 1/4 SE 1/4 NE 1/4 | 9 | T 30 S | R 33 EW |
| Distance and direction from nearest town or city? Jct. 83 & 56 go 3 W. on Hwy. 56, 1/2 S., 1/4 W. | | | Street address of well if located within city? | | |

| | | |
|---|--|--|
| 2 WATER WELL OWNER: Hobble Land & Cattle Co. | | Board of Agriculture, Division of Water Resources Application Number: |
| RR#, St. Address, Box #: 1667 No. Charles | | |
| City, State, ZIP Code: Wichita, KS 67203 | | |

| | |
|--|--|
| 3 DEPTH OF COMPLETED WELL: 416 ft. Bore Hole Diameter: 28 in. to in. to ft. | |
| Well Water to be used as: | 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 10 Observation well |
| Well's static water level: 306 ft. below land surface measured on March month 31 , day 1981 year | |
| Pump Test Data: Well water was 328 ft. after 1 hours pumping 1678 gpm | |
| Est. Yield 1700 gpm: Well water was ft. after hours pumping gpm | |

| | | | |
|--|---|---|--|
| 4 TYPE OF BLANK CASING USED: | | 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped | |
| 1 Steel 3 RMP (SR) | 6 Asbestos-Cement 9 Other (specify below) | Welded X | |
| 2 PVC 4 ABS | 7 Fiberglass | Threaded | |
| Blank casing dia: 16 in. to 297 ft. Dia in. to ft. Dia in. to ft. | Casing height above land surface: 12 in., weight 37 lbs./ft. Wall thickness or gauge No. 219 | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | 7 PVC 10 Asbestos-cement | |
| 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) | 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) | | |
| Screen or Perforation Openings Are: | | 5 Gauzed wrapped 8 Saw cut 11 None (open hole) | |
| 1 Continuous slot 3 Mill slot | 6 Wire wrapped 9 Drilled holes | | |
| 2 Louvered shutter 4 Key punched | 7 Torch cut 10 Other (specify) | | |
| Screen-Perforation Dia: 16 in. to 416 ft. Dia in. to ft. Dia in. to ft. | | | |
| Screen-Perforated Intervals: From ft. to ft. From ft. to ft. From ft. to ft. | | | |
| Gravel Pack Intervals: From ft. to ft. From ft. to ft. From ft. to ft. | | | |

| | | | |
|--|---|---|--|
| 5 GROUT MATERIAL: | | 1 Neat cement 2 Cement grout 3 Bentonite 4 Other | |
| Grouted Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. | | | |
| What is the nearest source of possible contamination: | | 10 Fuel storage 14 Abandoned water well | |
| 1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 15 Oil well/Gas well | 2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 16 Other (specify below) | | |
| 3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines Unknown | | | |
| Direction from well How many feet ? Water Well Disinfected? Yes X No | | | |
| Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample was submitted month day year: Pump Installed? Yes X No | | | |
| If Yes: Pump Manufacturer's name Layne & Bowler WellLine Model No. 12TLC HP 165 Volts | | | |
| Depth of Pump Intake 400 ft. Pumps Capacity rated at 1400 gal./min. | | | |
| Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other | | | |

| | |
|--|--|
| 6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on March month 20 , day 1981 year | |
| and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 | |
| This Water Record was completed on May month 12 , day 1981 year under the business name of Layne-Western Company, Inc. by (signature) <i>[Signature]</i> | |

| | | | | | | |
|--|------|---------------------|--------------------|------|-----|----------------------------|
| 7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: | FROM | TO | LITHOLOGIC LOG | FROM | TO | LITHOLOGIC LOG |
| | 0 | 38 | Clay | 424 | 446 | Yellow & white clay |
| | 38 | 76 | Red clay | 446 | 458 | Brown clay |
| | 76 | 82 | Clay | 458 | 516 | Shale w/hard spots at 516' |
| | 82 | 114 | Sand and gravel | | | |
| | 114 | 152 | Clay w/little sand | | | |
| | 152 | 160 | Cemented sand | | | |
| | 160 | 203 | Loose, medium sand | | | |
| 203 | 240 | Loose sand & gravel | | | | |
| 240 | 305 | Loose, medium sand | | | | |
| 305 | 416 | Loose sand & gravel | | | | |
| 416 | 424 | White rock | | | | |

| | | | | |
|-----------------------|--|--|--|--------------------------------|
| ELEVATION: 416 | | Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. | | (Use a second sheet if needed) |
|-----------------------|--|--|--|--------------------------------|

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

END

SEC.

9

SE 1/4 SE 1/4 NE 1/4