

LOCATION OF WATER WELL: County: HASKELL		Fraction $\frac{1}{4}$ CSW $\frac{1}{4}$ NE $\frac{1}{4}$	Township Number 13	Range Number 30 S R 33 E	
Distance and direction from nearest town or city street address of well if located within city? 2 W 2 1/2 S 1/2 W 1/4 N 1/4 E OF SUBLETTE, KS.					
WATER WELL OWNER: A MOCO PRODUCTION RR#, St. Address, Box #: 530 S. GRANT City, State, ZIP Code: WYSSA, KS 67880			JL KING #1 Board of Agriculture, Division of Water Resources Application Number: 1-83-311		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 380 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1... 282 ...ft. 2... ..ft. 3... ..ft. WELL'S STATIC WATER LEVEL 282 ...ft. below land surface measured on mo/day/yr 7-30-83 Pump test data: Well water was 300 ...ft. after 2 ...hours pumping 60 ...gpm Est. Yield 60 ...gpm: Well water wasft. afterhours pumpinggpm Bore Hole Diameter 9 ...in. to 380 ...ft., and.....in. toft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..✓; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ✓ No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ✓ Clamped Welded Threaded			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 ...in. to 300 ...ft., Dia.....in. toft., Dia.....in. toft.		7 Fiberglass			
Casing height above land surface.... 24 ...in., weight 200 ...lbs./ft. Wall thickness or gauge No. 0.265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 300 ...ft. to 380 ...ft., Fromft. toft.					
GRAVEL PACK INTERVALS: From 205 ...ft. to 380 ...ft., Fromft. toft.					
GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ...ft. to 10 ...ft., Fromft. toft., Fromft. toft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? EAST		How many feet? 200			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	282	OVERBURDEN			
282	320	MED. SAND			
320	345	Blue Clay			
345	380	MED. SAND			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/30/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 . This Water Well Record was completed on (mo/day/yr) 8/1/83 under the business name of P.W. WATER WELL SERVICE by (signature) <i>C.D. Wagner</i> INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					