

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Haskell		NW 1/4 NE 1/4 SW 1/4		23		T 30 S		R 33 EW	
Distance and direction from nearest town or city street address of well if located within city? From Hwy 83 & 56 junction West of Sublette 4 South, 1 West, 2500' North, 3800' West of Southeast corner of section									
2 WATER WELL OWNER: Bill Taylor									
RR#, St. Address, Box # : 1106 N. Country Club									
City, State, ZIP Code : Carlsbad, NM 88220									
Board of Agriculture, Division of Water Resources Application Number: 16416									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 520 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 289 ft. below land surface measured on mo/day/yr 04/26/90							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 30 in. to 520 ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)							
		Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded									
Blank casing diameter 16 in. to 310 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 310 ft. to 520 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 520 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NONE 13 Insecticide storage									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS	
		SEE ATTACHED LOG							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 17, 1990 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) June 22, 1990 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) <i>Kathy Olson</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4