


1 LOCATION OF WATER WELL		Fraction	Section Number		Township Number	Range Number
County: <u>Haskell</u>		<u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$	<u>24</u>		T <u>30</u> S	R <u>33</u> E/W
Distance and direction from nearest town or city? <u>10-55-04</u> <u>Sublette Ka</u>			Street address of well if located within city?			
2 WATER WELL OWNER: <u>Clifford Stapleton</u>						
RR#, St. Address, Box #: <u>R.R. Sublette Kansas 67877</u>			Board of Agriculture, Division of Water Resources			
City, State, ZIP Code			Application Number:			
3 DEPTH OF COMPLETED WELL: <u>410</u> ft. Bore Hole Diameter: <u>10</u> in. to <u>410</u> ft. and in. to ft.						
Well Water to be used as:						
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well						
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
7 Lawn and garden only 10 Observation well						
Well's static water level: <u>260</u> ft. below land surface measured on <u>9</u> month <u>20</u> day <u>80</u> year						
Pump Test Data: Well water was ft. after hours pumping gpm						
Est. Yield <u>30</u> gpm: Well water was <u>262</u> ft. after <u>2</u> hours pumping <u>13</u> gpm						
4 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: <u>Glued</u> Clamped						
2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
7 Fiberglass Threaded						
Blank casing dia <u>5</u> in. to <u>410</u> ft. Dia in. to ft. Dia in. to ft.						
Casing height above land surface: <u>24</u> in., weight lbs./ft. Wall thickness or gauge No. <u>25</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)						
12 None used (open hole)						
Screen or Perforation Openings Are:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
7 Torch cut 10 Other (specify)						
Screen-Perforation Dia <u>5</u> in. to ft. Dia in. to ft. Dia in. to ft.						
Screen-Perforated Intervals: From <u>340</u> ft. to <u>380</u> ft. From <u>380</u> ft. to <u>410</u> ft.						
Gravel Pack Intervals: From <u>13</u> ft. to <u>410</u> ft. From ft. to ft.						
5 GROUT MATERIAL:						
1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other						
Grouted Intervals: From <u>4</u> ft. to <u>14</u> ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well						
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well						
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)						
13 Watertight sewer lines						
Direction from well: <u>East</u> How many feet: <u>100</u> ? Water Well Disinfected? <u>Yes</u> No						
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? <u>Yes</u> No						
If Yes: Pump Manufacturer's name: <u>F. & W.</u> Model No. <u>158A20</u> HP <u>1 1/2</u> Volts <u>230</u>						
Depth of Pump Intake: <u>300</u> ft. Pumps Capacity rated at <u>13</u> gal./min.						
Type of pump: 1 <u>Submersible</u> 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other						
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on <u>9</u> month <u>20</u> day <u>80</u> year						
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>127</u>						
This Water Well Record was completed on <u>11</u> month <u>11</u> day <u>80</u> year under the business name of <u>Slodum Well Drilling</u> by (signature) <u>Paul Slodum</u>						
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		
		0 2 light loam				
		2 66 tan silt & caliche				
		66 100 sand coarse & gravel				
		100 156 clay silts & silt balls				
		156 280 sand coarse & gravel				
		280 328 blue shale				
		328 340 coarse sand calcified				
		340 380 " "				
		380 393 clays blue-tan				
		393 410 gravel fine w/sand coarse				
410 420 caliche like Hard Tan						
ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)						
INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						