


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Haskell	Township name Haskell	Fraction SE 1/4 of SE 1/4	Section number 25	Town number T S 30	Range number R W 33
Distance and direction from nearest town or city: South of Sublette, Ks. 5 miles Street address of well location if in city: ON Highway 83 West Side of road.			3 Owner of well: J.H. Chaffin Address: Sublette, Ks.			
Locate with "X" in section below: 			Sketch map:			4 Well depth: 406 ft. Date of completion 3-31-75 Well diameter 26 in.
2 Type and color of material			From			To
			5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
			6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>			
			7 Casing: Material Steel Weight: above/below Threading <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 407 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Weight 34.25 lbs./ft. 1 = in. to ft. depth			
			8 Screen: Johnson Division Manufacturer Type Galv. Dia. 16" Slot/groove Length 20' Set between 370 ft. and 390 ft. Perforations: 240-370, 390-406 Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 1/2" down			
			9 Static water level: 210 ft. below land surface Date 2-13-75			
			10 Pumping level below land surfaces: 229 ft. after 2 hrs. pumping 851 g.p.m. 235 ft. after 5 hrs. pumping 1250 g.p.m. Estimated maximum yield 1200 g.p.m.			
			11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date			
			12 Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade			
			13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Cement <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Clay Puddled Depth: From 0 ft. to 10 ft.			
			14 Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
			15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Peerless-FMC Model number G10442 HP 150 Volts Length of drop pipe 260 ft. capacity 800 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
16 Remarks: elevation Good Well. No Drilling Contamination. Customer Satisfied. Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley			17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co. 208 Business name License No. Address Box 493, Garden City, Ks. Signed [Signature] Date 4-23-75 Authorized representative			

Professional **WILSON DRILLING CO.** Incorporated
Irrigation and Domestic Water Systems Complete Installation and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

Haskell County J. H. Chaffin February 13, 1975

S. E. ³³ sec. 25 T. 30 R. 38 Static Water Level: 210 Test # 7

Location: From N. E. Corner of 1/4- 1/8 Mile South

- 0 2 Top Soil
- 2 68 Brown Clay
- 68 85 Fine to Medium Sand & Gravel (loose)
- 85 136 Brown Clay
- 136 280 Fine to Medium Sand & Gravel (Loose)
- 280 309 Brown Clay
- 309 320 Fine to Medium Sand & Gravel 10% Clay (Loose)
- 320 406 Fine to Medium Sand & Gravel (Loose)
- 406 425 Brown Clay & White Rock (Tight)