

MW5

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

1/4

1/4

1/4

1 LOCATION OF WATER WELL: County: HASKALL		Fraction: SW 1/4 SW 1/4 NE 1/4	Section Number: 13	Township Number: T 30 S	Range Number: R 34 EW																																																																																										
Distance and direction from nearest town or city street address of well if located within city? 204 W. HWY 56, SATANTA, KS 67870																																																																																															
2 WATER WELL OWNER: SATANTA QUICK AND EASY RR#, St. Address, Box #: 204 W. HWY 56 City, State, ZIP Code: SATANTA, KS 67870			Board of Agriculture, Division of Water Resources Application Number: 2966.77																																																																																												
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL: 330 ft. ELEVATION: 2966.77 Depth(s) Groundwater Encountered 1. 302 ft. 2. 305.57 ft. below land surface measured on mo/day/yr 05/28/97 WELL'S STATIC WATER LEVEL 305.57 ft. below land surface measured on mo/day/yr 05/28/97 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter 8 in. to 340 ft., and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No X _____; If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes _____ No X _____																																																																																													
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____ Blank casing diameter 4 in. to 295 ft., Dia. _____ in. to _____ ft., Dia. _____ in. to _____ ft. Casing height above land surface -6.0 in., weight 3.91 lbs./ft. Wall thickness or gauge No. 0.267 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) _____ 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From 295 ft. to 330 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From 292 ft. to 340 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft.																																																																																															
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____ Grout Intervals: From 1 ft. to 292 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) _____ Direction from well? NORTH How many feet? 20																																																																																															
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>0</td><td>14</td><td>SILTY CLAY</td><td></td><td></td><td></td></tr> <tr><td>14</td><td>19</td><td>SANDY SILT</td><td></td><td></td><td></td></tr> <tr><td>19</td><td>44</td><td>SILTY SAND</td><td></td><td></td><td></td></tr> <tr><td>44</td><td>70</td><td>SILTY CLAY</td><td></td><td></td><td></td></tr> <tr><td>70</td><td>80</td><td>SANDY CLAY</td><td></td><td></td><td></td></tr> <tr><td>80</td><td>100</td><td>SAND & GRAVEL</td><td></td><td></td><td></td></tr> <tr><td>100</td><td>110</td><td>CLAYEY SAND</td><td></td><td></td><td></td></tr> <tr><td>110</td><td>170</td><td>GRAVEL</td><td></td><td></td><td></td></tr> <tr><td>170</td><td>181</td><td>SAND</td><td></td><td></td><td></td></tr> <tr><td>181</td><td>233</td><td>CLAY</td><td></td><td></td><td></td></tr> <tr><td>233</td><td>260</td><td>SAND & GRAVEL</td><td></td><td></td><td></td></tr> <tr><td>260</td><td>284</td><td>SAND</td><td></td><td></td><td></td></tr> <tr><td>284</td><td>300</td><td>CLAY</td><td></td><td></td><td></td></tr> <tr><td>300</td><td>340</td><td>SAND & GRAVEL</td><td></td><td></td><td></td></tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	14	SILTY CLAY				14	19	SANDY SILT				19	44	SILTY SAND				44	70	SILTY CLAY				70	80	SANDY CLAY				80	100	SAND & GRAVEL				100	110	CLAYEY SAND				110	170	GRAVEL				170	181	SAND				181	233	CLAY				233	260	SAND & GRAVEL				260	284	SAND				284	300	CLAY				300	340	SAND & GRAVEL			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																										
0	14	SILTY CLAY																																																																																													
14	19	SANDY SILT																																																																																													
19	44	SILTY SAND																																																																																													
44	70	SILTY CLAY																																																																																													
70	80	SANDY CLAY																																																																																													
80	100	SAND & GRAVEL																																																																																													
100	110	CLAYEY SAND																																																																																													
110	170	GRAVEL																																																																																													
170	181	SAND																																																																																													
181	233	CLAY																																																																																													
233	260	SAND & GRAVEL																																																																																													
260	284	SAND																																																																																													
284	300	CLAY																																																																																													
300	340	SAND & GRAVEL																																																																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/14/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on (mo/day/yr) 06/18/97 under the business name of CORANCO INC by (signature) [Signature]																																																																																															
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																															