WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Haskell | Fraction: ¼ ¼ NE ¼ | Section Number: 2 | Township Number: T 30 S | Range Number: R 34 E (W)

Distance and direction from nearest town or city? Satanta 2¼ North + 1½ West - ½ South | Street address of well if located within city?

2 WATER WELL OWNER: Don Foster
RR#, St. Address, Box # :
City, State, ZIP Code :
Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL 527 ft. Bore Hole Diameter 26 in. to 527 ft., and in. to ft.

Well Water to be used as: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)

Well's static water level ft. below land surface measured on Pump Setter Done Test Pumping day year

Pump Test Data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)

Casing Joints: Glued Clamped Welded X Threaded

Blank casing dia 16 in. to 527 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight 36.4 lbs./ft. Wall thickness or gauge No .219

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

Screen-Perforation Dia 16 in. to 527 ft., Dia in. to ft., Dia in. to ft.

Screen-Perforated Intervals: Rsm. Screen 300 ft. to 380 ft., Rsm. Perf 380 ft. to 500 ft.
Rsm. Screen 515 ft. to 525 ft., Rsm. Perf 525 ft. to 527 ft.

Gravel Pack Intervals: From 10 ft. to 527 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Lateral lines 4 Cess pool 5 Seepage pit 6 Pit privy 7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage 13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Center of ¼ Section N/A

Direction from well How many feet ? Water Well Disinfected? Yes No X

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample was submitted month day year: Pump Installed? Yes No X

If Yes: Pump Manufacturer's name Model No. HP Volts
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on November month 20 day 1979 year, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208

This Water Well Record was completed on December month 11 day 1980 year under the business name of Minter Wilson Drilling Co., Inc. by (signature) Marlene DeKeyser Office Mgr

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		Test log attached			

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 34 E (W) SEC. 2 ¼ C of NE ¼

MINTER-WILSON DRILLING CO.
INCORPORATED

November 10, 1979

Don Foster
Haskell County

Location: NE¼ 2-30-34 Satanta West side 2 8/10 mile North on Black Top about 500' West offset 60 North west of well

Static Water Level - 275

Test #

0	3	Top Soil
3	13	Brown Clay
13	51	Brown Sandy Clay
51	67	Fine Sand Clay mixed
67	82	Brown Sandy Clay
82	100	Fine to med. sand & gravel streak of coarse gravel
100	117	Brown Sandy Clay
117	175	Fine to med. sand & gravel
175	191	Fine to med. sand & gravel small hard streak
191	202	Brown Sandy Clay
202	278	Fine to med. sand & gravel tight streak
278	290	Fine to med. sand & gravel tight 10% Clay
290	374	Fine to med. sand & gravel
374	385	Fine to med. sand & gravel small clay streak
385	412	Brown Sandy Clay
412	457	Brown Sandy Clay Tight
457	464	Fine to med. sand 20% Clay
464	503	Brown Sandy Clay Tight
503	517	Fine Sand 15% Clay Tight
517	527	Fine to med. sand & gravel small loose streak
527	552	Yellow Clay Brown Rock hard pull down
552	560	Shale hard pull down