

[1] LOCATION OF WATER WELL: County: Haskell		Fraction NE $\frac{1}{4}$ SE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 22	Township Number T 30 S	Range Number R 34 E/W
Distance and direction from nearest town or city street address of well if located within city? 3 miles West of Satanta and on left side of highway					
[2] WATER WELL OWNER: #3 Mosbarger		Gabbert & Jones		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		333 E. English #215			
City, State, ZIP Code :		Wichita, KS 67202		Application Number: T89-558	
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL . . . 400 ft.			
<p>A diagram showing a section box divided into four quadrants labeled NW, NE, SW, SE. An arrow points to the bottom-right corner (SW quadrant) where an 'X' is placed.</p>		ELEVATION:ft. Depth(s) Groundwater Encountered 1. 187 .ft. 2.ft. 3.ft. WELL'S STATIC WATER LEVEL 213 .ft. below land surface measured on mo/day/yr 12-8-89 Pump test data: Well water was 200 .ft. after 2 . hours pumping 65 . gpm Est. Yield 70 . gpm: Well water wasft. afterhours pumpinggpm Bore Hole Diameter 9 .in. to 400 .ft., andin. toft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No X ; If yes, mo/day/yr sample was sub-mitted Water Well Disinfected? Yes X No			
		[5] TYPE OF BLANK CASING USED:			
		Blank casing diameter 5 .in. to 300 .ft., Diain. toft., Diain. toft. Casing height above land surface 14 .in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265			
		TYPE OF SCREEN OR PERFORATION MATERIAL:			
		SCREEN OR PERFORATION OPENINGS ARE:			
SCREEN-PERFORATED INTERVALS: From 300 .ft. to 400 .ft., Fromft. toft. Fromft. toft., Fromft. toft. GRAVEL PACK INTERVALS: From 200 .ft. to 400 .ft., Fromft. toft. Fromft. toft., Fromft. toft.					
[6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>Hole plug</u>					
Grout Intervals: From 20 .ft. to 0 .ft., Fromft. toft., Fromft. toft.					
What is the nearest source of possible contamination:					
Direction from well? Southwest How many feet? 250					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	213	Overburden			
213	240	Medium sand			
240	260	Medium sand and gravel			
260	280	Medium sand			
280	300	Medium sand			
300	320	Medium sand			
320	340	Medium sand and gravel			
340	400	Medium sand			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-8-89 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 12-10-89					
under the business name of T & W Water Well Service, Inc. by (signature) <i>C.W. Wagner</i>					