



1 LOCATION OF WATER WELL: County: HASKEL		Fraction SE 1/4 SW 1/4 SE 1/4		Section Number 29	Township Number T 30 S	Range Number R 34 E/W
Distance and direction from nearest town or city street address of well if located within city? 3 1/2 West and 2 South of Satanta, Kansas						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Mr. Jim Jones R.R. #1, Box 69A Satanta, Kansas 67870 Board of Agriculture, Division of Water Resources Application Number: ---				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION: Slope Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 151 ft. below land surface measured on mo/day/yr Dec. 23, 1985 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 20 gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 220 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No				
						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) XX PVC 4 ABS Blank casing diameter 5 in. to 200 ft. Dia Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped XX Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
SCREEN-PERFORATED INTERVALS: From 200 ft. to 220 ft.		From ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS: From 10 ft. to 220 ft.		From ft. to ft. From ft. to ft.				
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination: NONE 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage				
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	4	Topsoil				
4	95	Clay				
95	170	Clay and Med. to Lar. Sand, Strippy Clay				
170	220	Med. to Lar. Sand and Gravel				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) January 22, 1986 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) January 23, 1986 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature) 						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						