		RECORD		WC-5				urces; App. No.			
		WATER WELL:	Fraction NW	1/ NE	Se	ction Nu	ımber	Township Nun	nber	Range Number	
County: Haskell SW ¼ NW ¼ NE ¼ 13 T 30 S R 34 (W) Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)											
located within city?											
Hwy 56 & Ponca Ave & Otoe St's, Satanta, KS Longitude:											
2 WATER WELL OWNER: McDonald's 66 - Scott McDonald Elevation: RR#, St. Address, Box # : PO Box 730 Elevation: Datum:											
RR#, S	t. Address,	Box # : PO Bo	X 73U VS 67070 073	20	שלו	atum:	otion N	lathad:			
City, State, ZIP Code : Satanta, KS 67870-0730 Data Collection Method: 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 350' ft.											
LOCATON LOCATE WELL'S 4 DEPTH OF COMPLETED WELL II.											
		N D = 41 (2) C ====	- 4to- Eto		22	n •	A 2	4		۵	
1	AN "X" I	Depth(s) Grou	nawater Encounte	real	~33	U'	n. 2	I	ι. 3	II.	
SECTI	WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 ~330' ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL NM ft. below land surface measured on mo/day/yr NM NM ft. below land surface measured on mo/day/yr NM										
	N Pump test data: Well water was ft. after hours pumping gpm										
Est. Yield gpm: Well water was ft. after hours pumping gpm											
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
W I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial / Domestic (lawn & garden) (10 Monitoring well)											
swsE											
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs											
S Sample was submitted Water Well Disinfected? Yes No X											
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped											
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded											
(2 PVC) 4 ABS 7 Fiberglass Threaded X											
(2 PVC) 4 ABS 7 Fiberglass Threaded X Blank casing diameter 4 in. to 320 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 48 in., Weight lbs./ft. Wall thickness or gauge No. Sch. 40 PVC											
Casing height above land surface 48 in., Weight lbs./ft. Wall thickness or gauge No. Sch. 40 PVC											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)											
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)											
ISCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot (3 Mill slot) 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)											
1 Continuous slot (3 Mill slot) 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 320 ft. to 350 ft. From ft. to ft.											
From A to A From A to											
From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 318 ft. to 360 ft. From ft. to ft.											
UNAVEL FACE INTERVALS: FIGHT 516 IL IO 500 IL FIOR IL IO IL.											
From ft. to ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite) 4 Other											
Grout Intervals From 1 ft. to 318 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? 12 Fertilizer storage 15 Oil well/ gas well How many feet? Lust Site											
Direction	from well?			How	many	reet?					
FROM	TO	LITHO	LOGIC LOG	FF	ROM	TO		PLUGGING			
0	76	Clay, silty			241		Sandy	, very fine to m	ediur	m	
76	95	Sand, very fine to			290	315			o coa	rse, angular pieces	
95	107	Sand, clayey, very f			315	345		fine to coarse			
107	120 150	Sand & gravel, fir Sand, very fine to			345 353	353 357	Clay	& gravel, quart	Z		
120 150	190	Sand, very fine to Sand, fine to coar			357	360		& gravel, very f	fine to	o coarse	
190	198	Sand & gravel, fir		,5 .	331	500	Danu (ce graves, very	inc t	o coarse	
198	217	Clay, sandy	20 10 0041 00								
217	222	Sand, fine to coar	se					M	W10		
222	241	Clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged											
under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on (2003/2008) . T											
1					-			at Hell		·	
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for											
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.											

KSA 82a-1212