

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Haskell		SW 1/4 SW 1/4 NE 1/4		2		T 30 S		R 34 SW			
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 mi. North, 1/2 mi. West, 3/4 Mi. North of Satanta											
2 WATER WELL OWNER: C. M. Light Estate Murfin Drilling, Inc.											
RR#, St. Address, Box #: Box 2797 P. O. Box 661 Board of Agriculture, Division of Water Resources											
City, State, ZIP Code: Liberal, KS 67901 Colby, KS 67701 Application Number: 980031											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 440 ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL 285 ft. below land surface measured on mo/day/yr									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter in. to ft. and in. to ft.									
WELL WATER TO BE USED AS:											
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded											
Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface. 4 in., weight lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 999 ft. to 999 ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From 6 ft. to 3 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? How many feet?											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
						440		285		Washed Sand	
						285		6		Clay	
						6		3		Bentonite	
						3		0		Topsoil	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-20-98 and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 5-20-98											
under the business name of Woofter Pump & Well, Inc. by (signature) <i>Ray C. Woofter</i>											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4