

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Haskell		NW 1/4 NW 1/4 NW 1/4	34	T 30 S	R 34 E/W
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Mike Garza					
RR#, St. Address, Box # :		Box 522		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Satanta, Ks. 67870		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 190 ft. below land surface measured on mo/day/yr 3-17-98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 75 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to 320 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
☒ PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 5 in. to 320 ft., Dia				8 Concrete tile	
Casing height above land surface 12 in., weight				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued ☒ Clamped	
1 Steel		3 Stainless steel		Welded	
2 Brass		4 Galvanized steel		Threaded	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		☒ Saw cut	
1 Continuous slot		6 Wire wrapped		11 None (open hole)	
2 Louvered shutter		7 Torch cut		10 Other (specify)	
4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 280 ft. to 320 ft., From		ft. to ft.	
		From ft. to ft., From		ft. to ft.	
GRAVEL PACK INTERVALS:		From 25 ft. to 190 ft., From		ft. to ft.	
		From 200 ft. to 320 ft., From		ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite chips Other					
Grout Intervals: From 5 ft. to 25 ft., From 190 ft. to 200 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
☒ Septic tank		4 Lateral lines		10 Livestock pens	
2 Sewer lines		5 Cess pool		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		12 Fertilizer storage	
		7 Pit privy		13 Insecticide storage	
		8 Sewage lagoon		14 Abandoned water well	
		9 Feedyard		15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well?				How many feet? 100	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	top soil			
1	5	brown silty clay			
5	122	coarse sand & gravel			
122	167	medium to coarse sand, cemented			
167	170	brown clay			
170	190	medium to coarse sand, small gravel			
190	200	gray clay			
200	215	gray clay with sand streaks			
215	273	medium to coarse sand & small gravel			
273	320	medium to coarse sand & gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-17-98 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 532 This Water Well Record was completed on (mo/day/yr) 3-24-98					
under the business name of Midwest Well & Pump by (signature) <i>Victor Soukup</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4