

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Waters #2

Inv. # 12245

1. Location of well:		County Grant	Fraction 1/4 NW 1/4 NW 1/4	Section number 23	Township number T 30 S	Range number R 35 E/W
2. Distance and direction from nearest town or city: west of Satanta, 6 west, 1/4 south			3. Owner of well: Rains & Williamson Oil Co., Inc. R.R. or street: 435 Page Court, 220 West Douglas City, state, zip code: Wichita, Kansas 67202			
4. Locate with "X" in section below:			Sketch map:			6. Bore hole dia. 9 in. Completion date 4-17-76 Well depth 260 ft.
						7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
5. Type and color of material			From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Surface			0	2	9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 28 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.78 lbs./ft. Dia 5 in. to 180 ft. depth Wall Thickness: inches or Dia 2 in. to 260 ft. depth gage No. 265	
Medium to large sand			2	105	10. Screen: Manufacturer's name sawed perf. Type PVC Dia. 5 in. Slot/gauze .030 Length 70 in. Set between 180 ft. and 250 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/8 to 3/16	
Clay			105	123	11. Static water level: 134 ft. below land surface Date 4-17-76	
Fine sand and medium to large sand			123	142	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 60 g.p.m.	
Clay, fine sand and medium to large sand			142	185	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date	
Medium to large sand			185	250	14. Well head completion: Pitless adapter 28 inches above grade	
Clay and medium to large sand 30-70			250	260	15. Well grouted? <input checked="" type="checkbox"/> yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
					16. Nearest source of possible contamination: ft. 100 Direction NE Type oilwell Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
					17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Carlile Water Well 118 Business name Box 275, Liberal, Ks. License No. Address Signed Edward E. Means Date 4-28 Authorized representative	
18. Elevation:			19. Remarks:			
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5